



Art.-Nr: WLREP3 Wireless Professional Repeater Höhere Reichweite

Wireless Professional Repeater

Dient der Verbindungsoptimierung innerhalb oder außerhalb von Gebäuden. Anwendung findet er bei ungünstigen Empfangsbedingungen oder weitläufigen Installationen. Die Reichweite zum nächsten Wireless Professional Teilnehmer beträgt wie die der Leuchten mindestens 30 Meter innerhalb von Gebäuden. Der WirelessProfessional-Funk-Repeater wird im IP65-Gehäuse geliefert

Repeater für automatisches Prüfsystem WirelessProfessional im 868 MHz-Band gemäß ETSI EN 300 220



Mehr Informationen

www.rp-group.com/de/item/WLREP3



TECHNISCHE DATEN

Material	Polycarbonate
Gehäusefarbe	Lichtgrau
Tiefe	76 mm
Breite	116 mm
Höhe	162 mm
Gewicht	0.42 kg
Zolltarifnummer	85176200
GTIN	4262483026717



Technical drawing of the ESD-1000 enclosure, showing multiple views with dimensions in mm:

- Top View:** Overall dimensions 179.9 mm (width) x 133.1 mm (depth). Internal width is 166.5 mm. Mounting hole spacing is 43.5 mm.
- Front View:** Overall height is 96.3 mm. Internal height is 108 mm. Mounting hole spacing is 77.7 mm. Mounting hole diameter is Ø25.
- Side View:** Overall width is 153.4 mm. Internal width is 128.2 mm. Mounting hole spacing is 147.7 mm. Mounting hole diameter is Ø25.
- Bottom View:** Overall dimensions 114 mm (width) x 89.6 mm (depth). Mounting hole spacing is 47.4 mm. Mounting hole diameter is Ø25.
- Isometric View:** Shows the enclosure with dimensions 153.4 mm (width) x 71.7 mm (depth) x 68.6 mm (height).
- Detail View:** Shows the mounting hole pattern with dimensions 25 mm (hole diameter), 20 mm (hole spacing), 16 mm (hole diameter), and 8 mm (hole spacing).
- Detail View:** Shows the mounting hole pattern with dimensions 40 mm (hole diameter), 32 mm (hole spacing), 25 mm (hole diameter), 16 mm (hole diameter), and 8 mm (hole spacing).

www.rp-group.com