



Art.-Nr: WLREP3 Wireless Professional Repeater

Wireless Professional Repeater

Dient der Verbindungsoptimierung innerhalb oder außerhalb von Gebäuden. Anwendung findet er bei ungünstigen Empfangsbedingungen oder weitläufigen Installationen. Die Reichweite zum nächsten Wireless Professional Teilnehmer beträgt wie die der Leuchten mindestens 30 Meter innerhalb von Gebäuden. Der WirelessProfessional-Funk-Repeater wird im IP65-Gehäuse geliefert

Repeater für automatisches Prüfsystem WirelessProfessional im 868 MHz-Band gemäß ETSI EN 300 220

Mehr Informationen
www.rp-group.com/de/item/WLREP3



TECHNISCHE DATEN

Material	Kunststoff
Gehäusefarbe	Lichtgrau
Tiefe	76 mm
Breite	116 mm
Höhe	162 mm
Gewicht	0.42 kg
Zolltarifnummer	85176200
GTIN	4262483026717



Technical drawing of the ESD-1000 enclosure, showing multiple views with dimensions in mm:

- Top View:** Overall dimensions 179.9 mm (width) x 133.1 mm (depth). Internal width is 166.5 mm. Mounting hole spacing is 43.5 mm. Mounting holes are Ø25. A central circular feature has a diameter of Ø40.
- Bottom View:** Overall dimensions 179.9 mm (width) x 133.1 mm (depth). Internal width is 166.5 mm. Mounting hole spacing is 43.5 mm. Mounting holes are Ø25. A central circular feature has a diameter of Ø40.
- Front View:** Overall height is 96.3 mm. Internal height is 108 mm. Mounting hole spacing is 77.7 mm. Mounting holes are Ø25. A central circular feature has a diameter of Ø40.
- Rear View:** Overall height is 96.3 mm. Internal height is 108 mm. Mounting hole spacing is 77.7 mm. Mounting holes are Ø25. A central circular feature has a diameter of Ø40.
- Side View:** Overall width is 153.4 mm. Internal width is 128.2 mm. Mounting hole spacing is 147.7 mm. Mounting holes are Ø25. A central circular feature has a diameter of Ø40.
- Isometric View:** Shows the enclosure from a three-quarter perspective, highlighting its compact design and mounting features.
- Detail Views:**
 - 6x:** Shows six mounting holes with a diameter of Ø25 and a spacing of 25 mm.
 - 4x:** Shows four mounting holes with a diameter of Ø25 and a spacing of 25 mm.

www.rp-group.com