



Art.-Nr: KXU029

**Exit sign, Emergency light Centralised power supply systems
Universal, CPS, 30 m, IP40, Polycarbonate, White, Set of
pictograms, Universal mounting**

Innovative plastic emergency exit sign luminaire for universal mounting, in a conically tapering housing producing an appealing look. Suited to inscription on one or two sides.



Planning certainty is provided by tool-free, variable use of the pictograms on site. A set of pictograms corresponding to DIN ISO 7010 (arrow to the right, left, up and down) is supplied as standard. Universal mounting includes fitting on the wall and ceiling as well as the option of fitting in the ceiling in conjunction with the mounting frame available.



More information
www.rp-group.com/en/item/KXU029



TECHNICAL DATA

Luminaire type	Exit sign, Emergency light
Mounting	Universal
Recognition distance	30 m
Pictograph	Set
Illuminant	LED
Housing material	Polycarbonate
Housing color	White
Protection type (IP)	IP40
Impact resistance (IK)	≥ 3
Certification	WEEE, CE, ENEC, TÜV Rheinland Type approved
Insulation class	2
Supply	Centralised power supply systems
Monitoring	Without monitoring
Bridging time	CPS
Battery	/
Operating mode	Permanent circuit
Input voltage AC	230 V



Input frequency	50 / 60 Hz
Input voltage DC	100-254 V
Power max.	4,6 W
Power maintained	4,6 W
Power non-maintained	0 W
Ambient temperature maintained mode	-25 °C to 40 °C
Ambient temperature non-maintained mode	-25 °C to 40 °C
Depth	48 mm
Width	332 mm
Height	242 mm
Weight	0.85
Weight incl. packaging	0.96
Connection cross-section	1.5 mm ²
Switching input	No
Emergency light blocking	No
Battery connection	No
Dimming function	No
Luminous flux mains	520 lm
Luminous flux emergency	520 lm
EOF	1
Customs tariff number	94056120
GTIN	4260123685881




Technical drawings of the 'EXIT' sign, showing front and side views with dimensions.

Front View (Top): The sign is rectangular with a total width of 332 and a total height of 242. It features a top section with two horizontal lines, a central panel with a downward arrow and a running figure, and a bottom section with a width of 312 and a height of 170. The top section has a height of 72.

Side View (Top): The sign has a total width of 48 and a total height of 10. It features a top section with a width of 48 and a height of 10, and a bottom section with a width of 10 and a height of 10.

Front View (Bottom): The sign is rectangular with a total width of 332 and a total height of 242. It features a top section with two horizontal lines, a central panel with a downward arrow and a running figure, and a bottom section with a width of 312 and a height of 170. The top section has a height of 72.

Side View (Bottom): The sign has a total width of 48 and a total height of 10. It features a top section with a width of 48 and a height of 10, and a bottom section with a width of 10 and a height of 10.



KXE-EB - Installation frame for KX emergency lights: Elegant recessed wall mounting

AWX001 - AWX wall bracket for emergency lights - 90° flag mounting

DSA - Wire suspension

2PW-EB - Pendant

2DW-EB - Pre-assembled designer pendant pair with fixed canopy, 4-core, white

KXBE - Concrete installation box for ceiling formwork installation for emergency lighting

www.rp-group.com