RP GROUP
SOLUTIONS IN SAFETY + LIGHTING

Art.-Nr: LSW019ML
Exit sign Centralised power supply systems Wall mounting, Central power supply (ML), CPS, 56 m, IP40, Aluminum, Anodised aluminium, Piktogram as reqired



Robust emergency exit sign luminaire made from slim aluminium profile, for wall mounting.

The additional downward light emission helps to illuminate emergency and escape routes.

Control and monitoring via central power supply system. The requested pictogram (arrow to the right, left, up or down) is supplied as standard.

CE

More information
www.rp-group.com/en/item/LSW019ML

TECHNICAL DATA


Luminaire type	Exit sign
Mounting	Wall mounting
Recognition distance	56 m
Pictograph	acc. to Specification
Illuminant	LED
Housing material	Aluminum
Housing color	Anodised aluminium
Protection type (IP)	IP40
Impact resistance (IK)	≥ 3
Certification	Waste disposal, CE
Insulation class	1
Supply	Centralised power supply systems
Monitoring	Central power supply (ML)
Bridging time	CPS
Battery	/
Operating mode	single luminaire switching
Input voltage AC	230 V
Input frequency	50 / 60 Hz
Input voltage DC	216 V



RP GROUP
SOLUTIONS IN SAFETY + LIGHTING

Power max.	9,3 W
Power maintained	9,3 W
Power non-maintained	1,1 W
Ambient temperature maintained mode	-20 °C to 40 °C
Ambient temperature non-maintained mode	-20 °C to 40 °C
Depth	62 mm
Width	614 mm
Height	334 mm
Weight	2.85
Weight incl. packaging	2.9
Connection cross-section	2.5 mm²
Switching input	Yes
Emergency light blocking	No
Battery connection	No
Dimming function	Yes
Luminous flux mains	600 lm
Luminous flux emergency	600 lm
Customs tariff number	94056180
GTIN	4260123682774

TECHNICAL DRAWING



RELATED PRODUCTS

Art.-No.	Image	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote maintenance	max. luminaires	Single luminaire monitoring

As of: 13.11.2026 - Subject to technical changes and errors.