



Art.-Nr: PFW013

Exit sign Self-contained

Wall mounting, 3 h, 24 m, IP65, Polycarbonate, White, Set of pictograms, Flexiklick

Robust plastic emergency exit sign or safety luminaire.

Use as an emergency exit sign luminaire for wall mounting.

Or without the use of pictograms as a safety luminaire with the prismatic cover included, preferably for ceiling mounting.

Planning certainty is provided by tool-free, variable use of the pictograms on site. A set of pictograms corresponding to DIN ISO 7010 (arrow to the right, left and down) is supplied as standard. The luminaire is fitted with the innovative flexible plug-in system for rapid use of the right lens. The corridor lens is supplied with every luminaire. A round lens, spotlight lens and beam lens are available as options.



More information

www.rp-group.com/en/item/PFW013



TECHNICAL DATA

Luminaire type	Exit sign
Mounting	Wall mounting
Recognition distance	24 m
Pictograph	Set
Illuminant	LED
Housing material	Polycarbonate
Housing color	White
Protection type (IP)	IP65
Impact resistance (IK)	5
Certification	WEEE, CE, D-Sign
Insulation class	1
Supply	Self-contained
Monitoring	ECB
Bridging time	3 h
Battery	NIMH 4,8 V/2,0 Ah
Operating mode	Non-maintained / maintained



Input voltage AC	230 V
Input frequency	50 / 60 Hz
Power max.	6,1 W
Power maintained	4,5 W
Power non-maintained	0,35 W
Ambient temperature maintained mode	-5 °C to 40 °C
Ambient temperature non-maintained mode	-5 °C to 40 °C
Depth	370 mm
Width	105 mm
Height	152 mm
Weight	1.07
Weight incl. packaging	1.2
Connection cross-section	2.5 mm ²
Switching input	Yes
Emergency light blocking	Yes
Battery connection	Connector
Dimming function	Yes
Luminous flux mains	220 lm
Luminous flux emergency	150 lm
Customs tariff number	94056120
GTIN	4260123686505



TECHNICAL DRAWING



ACCESSORY LIST

BALL2 - Wire mesh guard



RELATED PRODUCTS

Art.-No.	Image	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote maintenance	max. luminaires	Single luminaire monitoring
PFW013-COOL		ECB		RAL 9003						
PFW013-COOLIP54		ECB		RAL 9003						
PFW013-EHE		ECB		RAL 9003						
PFW013BC		Bus control		RAL 9003						
PFW013SC		SelfControl (SC)	Single battery	RAL 9003	€	no	high	no	unlimited	itself
PFW013SC-COOL		SelfControl (SC)	Single battery	RAL 9003	€	no	high	no	unlimited	itself
PFW013SC-COOLIP54		SelfControl (SC)	Single battery	RAL 9003	€	no	high	no	unlimited	itself
PFW013SC-EHE		SelfControl (SC)	Single battery	RAL 9003	€	no	high	no	unlimited	itself
PFW013SC-P		SelfControl (SC)	Single battery	RAL 9003	€	no	high	no	unlimited	itself
PFW013WL		Wireless Professional (WL)	self contained	RAL 9003	€€	yes	low	yes	1,000 per system	central
PFW013WL-COOLIP54		Wireless Professional (WL)	self contained	RAL 9003	€€	yes	low	yes	1,000 per system	central



Art.-No.	Image	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote maintenance	max. luminaires	Single luminaire monitoring
PFW013WL-EHE		Wireless Professional (WL)	self contained	RAL 9003	€€	yes	low	yes	1,000 per system	central
PFW013WL-P		Wireless Professional (WL)	self contained	RAL 9003	€€	yes	low	yes	1,000 per system	central
PFW013WL-P-COOLIP54		Wireless Professional (WL)	self contained	RAL 9003	€€	yes	low	yes	1,000 per system	central
PFW013WL-P-EHE		Wireless Professional (WL)	self contained	RAL 9003	€€	yes	low	yes	1,000 per system	central
PFW413WL		Wireless Professional (WL)	self contained	RAL 9003	€€	yes	low	yes	1,000 per system	central

As of: 23.07.2026 - Subject to technical changes and errors.