



Art.-Nr: PFW124

Exit sign Centralised power supply systems

Wall mounting, Without monitoring, CPS, 24 m, IP65,

Polycarbonate, White

Robust plastic emergency exit sign or safety luminaire.

Use as an emergency exit sign luminaire for wall mounting.

Or without the use of pictograms as a safety luminaire with the prismatic cover included, preferably for ceiling mounting.

Planning certainty is provided by tool-free, variable use of the pictograms on site.

A set of pictograms corresponding to DIN ISO 7010 (arrow to the right, left and down) is supplied as standard. The luminaire is fitted with the innovative flexible plug-in system for rapid use of the right lens. The hall lens is supplied with every luminaire. A round lens, spotlight lens and beam lens are available as options.



More information

www.rp-group.com/en/item/PFW124



TECHNICAL DATA


Luminaire type	Exit sign
Mounting	Wall mounting
Recognition distance	24 m
Pictograph	Set
Illuminant	LED
Housing material	Polycarbonate
Housing color	White
Protection type (IP)	IP65
Impact resistance (IK)	5
Certification	WEEE, CE, D-Sign
Insulation class	1
Supply	Centralised power supply systems
Monitoring	Without monitoring
Bridging time	CPS
Battery	/
Operating mode	Non-maintained / maintained
Input voltage AC	24 V



Input frequency	50 / 60 Hz
Input voltage DC	9-30 V
Power max.	4,2 W
Power maintained	4,2 W
Power non-maintained	- W
Ambient temperature maintained mode	-25 °C to 40 °C
Ambient temperature non-maintained mode	-25 °C to 40 °C
Depth	370 mm
Width	105 mm
Height	152 mm
Weight	0.91
Weight incl. packaging	1.04
Connection cross-section	1.5 mm ²
Switching input	No
Emergency light blocking	No
Battery connection	No
Dimming function	No
Luminous flux mains	340 lm
Luminous flux emergency	340 lm
Customs tariff number	94056120
GTIN	4260659563318



TECHNICAL DRAWING



ACCESSORY LIST

BALL2 - Wire mesh guard

As of: 05.09.2025 - Subject to technical changes and errors.