



Art.-Nr: U6E124

Exit sign Centralised power supply systems

**Recessed wall mounting, Without monitoring, CPS, 22 m,
IP40, Metal, White**

Metal emergency exit sign luminaire integrated into the wall.

Planning certainty is provided by tool-free, variable use of the pictograms on site.

A set of pictograms corresponding to DIN ISO 7010 (arrow to the right, left, up and down) is supplied as standard.



More information

www.rp-group.com/en/item/U6E124



TECHNICAL DATA


Luminaire type	Exit sign
Mounting	Recessed wall mounting
Recognition distance	22 m
Pictograph	Set
Illuminant	LED
Housing material	Metal
Housing color	White
Protection type (IP)	IP40
Impact resistance (IK)	≥ 3
Certification	WEEE, CE
Insulation class	1
Supply	Centralised power supply systems
Monitoring	Without monitoring
Bridging time	CPS
Battery	/
Operating mode	Non-maintained / maintained
Input voltage AC	24 V
Input frequency	50 / 60 Hz
Input voltage DC	9-30 V
Power max.	4,2 W
Power maintained	4,2 W



Power non-maintained	- W
Ambient temperature maintained mode	-25 °C to 40 °C
Ambient temperature non-maintained mode	-25 °C to 40 °C
Depth	65 mm
Width	280 mm
Height	160 mm
Installation length	239 mm
Installation width	128 mm
Installation height	65 mm
Weight	1.04
Weight incl. packaging	1.31
Connection cross-section	1.5 mm ²
Switching input	No
Emergency light blocking	No
Battery connection	No
Dimming function	No
Luminous flux mains	340 lm
Luminous flux emergency	340 lm
Customs tariff number	94056180
GTIN	4260659563790



TECHNICAL DRAWING



ACCESSORY LIST

U6BE -

As of: 05.09.2025 - Subject to technical changes and errors.