



Art.-Nr: SKS2101WL
Emergency light Self-contained
Wall mounting, 1 h, IP54, Metal, Light grey

Compact emergency floodlight equipped with two freely adjustable metal safety luminaires. Suited to use indoors and, subject to certain conditions, to use outdoors.

Wireless central control and monitoring for large installations of up to 50,000 luminaires with Wireless Professional.



More information
www.rp-group.com/en/item/SKS2101WL



TECHNICAL DATA


Luminaire type	Emergency light
Mounting	Wall mounting
Pictograph	No
Illuminant	LED
Housing material	Metal
Housing color	Light grey
Protection type (IP)	IP54
Impact resistance (IK)	≥ 3
Certification	WEEE, CE
Insulation class	1
Supply	Self-contained
Monitoring	Wireless Professional (WL)
Bridging time	1 h
Battery	AGM - OGIV 12V 12 V/7 Ah
Operating mode	Non-maintained
Input voltage AC	230 V
Input frequency	50 / 60 Hz
Input voltage DC	12 V
Power max.	11,5 W
Power non-maintained	9,2 W
Ambient temperature maintained mode	-5 °C to 40 °C



Ambient temperature non-maintained mode	-5 °C to 40 °C
Depth	120 mm
Width	300 mm
Height	300 mm
Weight	9.12
Weight incl. packaging	9.87
Connection cross-section	2.5 mm ²
Switching input	No
Emergency light blocking	No
Battery connection	Clip
Dimming function	No
Luminous flux emergency	2 x 900 lm
Customs tariff number	94054239
GTIN	4260659563752



TECHNICAL DRAWING



RELATED PRODUCTS

Art.-No.	Image	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote maintenance	max. luminaires	Single luminaire monitoring
SKS2101SC		SelfControl (SC)	Single battery	RAL 7035	€	no	high	no	unlimited	itself

As of: 24.08.2026 - Subject to technical changes and errors.