Art.-Nr: ROPA4201ML
General light, Emergency light Centralised power supply systems
Ceiling mounting, Central power supply (ML), CPS, IP20, Metal, White

LED ceiling panel for general-purpose lighting with integrated safety light function for illuminating escape and emergency routes. The cover is made from PMMA plastic and is therefore UV-resistant, which prevents yellowing.

Control and monitoring via central power supply system.



More information
www.rp-group.com/en/item/ROPA4201ML

TECHNICAL DATA

Luminaire type	General light, Emergency light
Mounting	Ceiling mounting
Pictograph	No
Illuminant	LED
Housing material	Metal
Housing color	White
Protection type (IP)	IP20
Impact resistance (IK)	≥ 3
Certification	WEEE, CE
Insulation class	2
Supply	Centralised power supply systems
Monitoring	Central power supply (ML)
Bridging time	CPS
Battery	/
Operating mode	Non-maintained / maintained
Input voltage AC	230 V
Input frequency	50 / 60 Hz
Input voltage DC	216 V
Power max.	38 W

Power maintained	38 W
Power non-maintained	1,5 W
Ambient temperature maintained mode	0 °C to 40 °C
Ambient temperature non-maintained mode	0 °C to 40 °C
Depth	620 mm
Width	620 mm
Height	10 mm
Weight	3.67
Weight incl. packaging	4.07
Connection cross-section	2.5 mm²
Switching input	Yes
Emergency light blocking	No
Battery connection	No
Dimming function	No
Luminous flux mains	3600 lm
Luminous flux emergency	3600 lm
EOF	1
Customs tariff number	94054210
GTIN	4260581710439

RELATED PRODUCTS

Art.-No.	Image	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote maintenance	max. luminaires	Single luminaire monitoring
ROPA4201		Without monitoring		RAL 9003						
ROPA4201SC		SelfControl (SC)	Single battery	RAL 9003	€	no	high	no	unlimited	itself

As of: 26.08.2026 - Subject to technical changes and errors.