RP GROUP
SOLUTIONS IN SAFETY + LIGHTING

## Art.-Nr: ROPA4201SC
## General light, Emergency light Self-contained
## Ceiling mounting, SelfControl (SC), 3 h, IP20, Metal, White



LED ceiling panel for general-purpose lighting with integrated safety light function for illuminating escape and emergency routes. The cover is made from PMMA plastic and is therefore UV-resistant, which prevents yellowing.

Automatic monitoring of safety luminaire with SelfControl.

CE

More information
www.rp-group.com/en/item/ROPA4201SC

## TECHNICAL DATA

| | |
|---|---|
| Luminaire type | General light, Emergency light |
| Mounting | Ceiling mounting |
| Pictograph | No |
| Illuminant | LED |
| Housing material | Metal |
| Housing color | White |
| Protection type (IP) | IP20 |
| Impact resistance (IK) | ≥ 3 |
| Certification | WEEE, CE |
| Insulation class | 2 |
| Supply | Self-contained |
| Monitoring | SelfControl (SC) |
| Bridging time | 3 h |
| Battery | NIMH 4,8 V/4,0 Ah |
| Operating mode | Non-maintained / maintained |
| Input voltage AC | 230 V |
| Input frequency | 50 Hz |
| Input voltage DC | - V |
| Power max. | 36 W |

| | |
|---|---|
| Power maintained | 33 W |
| Power non-maintained | 2 W |
| Ambient temperature maintained mode | 0 °C to 40 °C |
| Ambient temperature non-maintained mode | 0 °C to 40 °C |
| Depth | 620 mm |
| Width | 620 mm |
| Height | 10 mm |
| Weight | 3.7 |
| Weight incl. packaging | 4.1 |
| Connection cross-section | 1.5 mm² |
| Switching input | Yes |
| Emergency light blocking | No |
| Battery connection | Clip |
| Dimming function | No |
| Luminous flux mains | 3600 lm |
| Luminous flux emergency | 660 lm |
| EOF | 0.18 |
| Customs tariff number | 94054210 |
| GTIN | 4260349828307 |

## RELATED PRODUCTS

| Art.-No. | Image | Monitoring | Supply | Color | Investment | Automatic log | Maintenance level | Remote maintenance | max. luminaires | Single luminaire monitoring |
|---|---|---|---|---|---|---|---|---|---|---|
| ROPA4201 |  | Without monitoring | | RAL 9003 | | | | | | |
| ROPA4201ML |  | Central power supply (ML) | Central power supply | RAL 9003 | €€€ | Yes | low | Yes | 1,920 per system | central |

As of: 26.08.2026 - Subject to technical changes and errors.