



Art.-Nr: ROPA4201SC
General light, Emergency light Self-contained
Ceiling mounting, SelfControl (SC), 3 h, IP20, Metal, White

LED ceiling panel for general-purpose lighting with integrated safety light function for illuminating escape and emergency routes. The cover is made from PMMA plastic and is therefore UV-resistant, which prevents yellowing.

Automatic monitoring of safety luminaire with SelfControl.



More information
www.rp-group.com/en/item/ROPA4201SC



TECHNICAL DATA

Luminaire type	General light, Emergency light
Mounting	Ceiling mounting
Pictograph	No
Illuminant	LED
Housing material	Metal
Housing color	White
Protection type (IP)	IP20
Impact resistance (IK)	≥ 3
Certification	WEEE, CE
Insulation class	2
Supply	Self-contained
Monitoring	SelfControl (SC)
Bridging time	3 h
Battery	NIMH 4,8 V/4,0 Ah
Operating mode	Non-maintained / maintained
Input voltage AC	230 V
Input frequency	50 Hz
Input voltage DC	- V
Power max.	36 W



Power maintained	33 W
Power non-maintained	2 W
Ambient temperature maintained mode	0 °C to 40 °C
Ambient temperature non-maintained mode	0 °C to 40 °C
Depth	620 mm
Width	620 mm
Height	10 mm
Weight	3.7
Weight incl. packaging	4.1
Connection cross-section	1.5 mm ²
Switching input	Yes
Emergency light blocking	No
Battery connection	Clip
Dimming function	No
Luminous flux mains	3600 lm
Luminous flux emergency	660 lm
EOF	0.18
Customs tariff number	94054210
GTIN	4260349828307

RELATED PRODUCTS

Art.-No.	Image	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote maintenance	max. luminaires	Single luminaire monitoring
ROPA4201		Without monitoring		RAL 9003						
ROPA4201ML		Central power supply (ML)	Central power supply	RAL 9003	€€€	Yes	low	Yes	1,920 per system	central

As of: 04.07.2026 - Subject to technical changes and errors.