



**Art.-Nr: XGIU009**

**Emergency light Centralised power supply systems  
Universal, CPS, IP66, Aluminum die-cast, Glass, Yellow (RAL  
1003)**



Glass cylinder safety luminaire with explosion protection for gas and dust Ex zones.

Prepared for two cable entries for feed-through wiring. By attaching a pictogram, can also be used as an emergency exit sign luminaire.

By means of mounting adapter for wall/ceiling mounting or suspension by means of eye bolt.

Labelling according to 2014/34/EC (ATEX)

Zone 1 / zone 21 gas and dust

- Ex d IIB T6 Gb / Ex d IIB T6 Gb
- Ex t IIIC T85°C Db

Manufactured in accordance with:

-EN 60079-0:2018, EN 60079-1:2014, EN 60079-31:2014

-Certified by INERIS 20ATEX0005X



More information  
[www.rp-group.com/en/item/XGIU009](http://www.rp-group.com/en/item/XGIU009)



## TECHNICAL DATA

|                        |                                  |
|------------------------|----------------------------------|
| Luminaire type         | Emergency light                  |
| Mounting               | Universal                        |
| Pictograph             | No                               |
| Illuminant             | LED                              |
| Housing material       | Aluminum die-cast, Glass         |
| Housing color          | Yellow (RAL 1003)                |
| Protection type (IP)   | IP66                             |
| Impact resistance (IK) | 7                                |
| Certification          | WEEE, CE, Explosion-protected    |
| Insulation class       | 1                                |
| Supply                 | Centralised power supply systems |



|                                         |                     |
|-----------------------------------------|---------------------|
| Monitoring                              | Without monitoring  |
| Bridging time                           | CPS                 |
| Battery                                 | /                   |
| Operating mode                          | Permanent circuit   |
| Input voltage AC                        | 230 V               |
| Input frequency                         | 50 / 60 Hz          |
| Power max.                              | 11 W                |
| Power maintained                        | 11 W                |
| Ambient temperature maintained mode     | -20 °C to 55 °C     |
| Ambient temperature non-maintained mode | -20 °C to 55 °C     |
| Depth                                   | 485 mm              |
| Width                                   | 157 mm              |
| Height                                  | 197 mm              |
| Weight                                  | 4.28                |
| Weight incl. packaging                  | 4.78                |
| Connection cross-section                | 2.5 mm <sup>2</sup> |
| Switching input                         | No                  |
| Emergency light blocking                | No                  |
| Battery connection                      | No                  |
| Dimming function                        | No                  |
| Luminous flux mains                     | 1200 lm             |
| Luminous flux emergency                 | 1200 lm             |
| Customs tariff number                   | 94051190            |
| GTIN                                    | 4260659564285       |



## TECHNICAL DRAWING



## ACCESSORY LIST

- X-KE001 - Professional installation components for emergency lighting systems
- X-KO001 - High-quality electronic assembly part 36x38 mm for emergency lighting
- X-MB001 - High-quality mounting element for emergency lighting modules (105 x 20 mm)
- X4N - Pictogram set with metal bracket for emergency lights XI, XM and XG

As of: 24.08.2026 - Subject to technical changes and errors.