



**Art.-Nr: XGXU013SC**  
**Emergency light Self-contained**  
**Universal, 3 h, IP66, Aluminum die-cast, Glass, Yellow (RAL 1003)**



Glass cylinder safety luminaire with explosion protection for gas and dust Ex zones.

Prepared for two cable entries for feed-through wiring. By attaching a pictogram, can also be used as an emergency exit sign luminaire.

By means of mounting adapter for wall/ceiling mounting or suspension by means of eye bolt.

Labelling according to 2014/34/EC (ATEX)

Zone 1 / zone 21 gas and dust

- Ex d IIB T6 Gb / Ex d IIB T6 Gb
- Ex t IIIC T85°C Db

Manufactured in accordance with

-EN 60079-0:2018, EN 60079-1:2014, EN 60079-31:2014

-Certified by INERIS 20ATEX0005X

Automatic monitoring of safety luminaire with SelfControl.



More information

[www.rp-group.com/en/item/XGXU013SC](http://www.rp-group.com/en/item/XGXU013SC)



## TECHNICAL DATA

|                        |                               |
|------------------------|-------------------------------|
| Luminaire type         | Emergency light               |
| Mounting               | Universal                     |
| Pictograph             | No                            |
| Illuminant             | LED                           |
| Housing material       | Aluminum die-cast, Glass      |
| Housing color          | Yellow (RAL 1003)             |
| Protection type (IP)   | IP66                          |
| Impact resistance (IK) | 7                             |
| Certification          | WEEE, CE, Explosion-protected |
| Insulation class       | 1                             |
| Supply                 | Self-contained                |
| Monitoring             | SelfControl (SC)              |



|                                         |                             |
|-----------------------------------------|-----------------------------|
| Bridging time                           | 3 h                         |
| Battery                                 | 6 V/4Ah Ah                  |
| Operating mode                          | Non-maintained / maintained |
| Input voltage AC                        | 230 V                       |
| Input frequency                         | 50 / 60 Hz                  |
| Power max.                              | 45 W                        |
| Power maintained                        | 45 W                        |
| Power non-maintained                    | 3 W                         |
| Ambient temperature maintained mode     | 0 °C to 55 °C               |
| Ambient temperature non-maintained mode | 0 °C to 55 °C               |
| Depth                                   | 1360 mm                     |
| Width                                   | 157 mm                      |
| Height                                  | 197 mm                      |
| Weight                                  | 5.5                         |
| Weight incl. packaging                  | 6.7                         |
| Connection cross-section                | 2.5 mm <sup>2</sup>         |
| Switching input                         | No                          |
| Emergency light blocking                | Yes                         |
| Battery connection                      | Clip                        |
| Dimming function                        | No                          |
| Luminous flux mains                     | 4600 lm                     |
| Luminous flux emergency                 | 750 lm                      |
| Customs tariff number                   | 94051190                    |
| GTIN                                    | 4260659564438               |



## TECHNICAL DRAWING



## ACCESSORY LIST

- X-K0001 - High-quality electronic assembly part 36x38 mm for emergency lighting
- X-MB001 - High-quality mounting element for emergency lighting modules (105 x 20 mm)
- X-KE001 - Professional installation components for emergency lighting systems
- X4N - Pictogram set with metal bracket for emergency lights XI, XM and XG

As of: 24.07.2026 - Subject to technical changes and errors.