RP GROUP
SOLUTIONS IN SAFETY + LIGHTING

Art.-Nr: YMOCA-BOX
Casambi ASD Outdoor Box with switch relay for surface mounting

Use the YMOCA-BOX as the main switch for all modules and luminaires and at the same time enjoy the positive side effect of using less power. The YMOCA-BOX can be used to switch all modules in a fully de-energised manner so that no standby current is consumed when switched off. In storage facilities or production areas with large numbers of floodlights and modules, you can therefore benefit from huge energy savings.



CE

More information
www.rp-group.com/en/item/YMOCA-BOX

TECHNICAL DATA

Dimensions	
Product dimensions Length	162 mm
Product dimensions Width	116 mm
Product dimensions Height	76 mm
Product weight	0.43 g
Packaging dimensions	
Packaging dimensions Length	190 mm
Packaging dimensions Width	135 mm
Packaging dimensions Height	90 mm
Weight incl. packaging	0.5 g
Color	
Color	Light grey
Housing material	
Housing material	Polycarbonate
Certification	
Certification	CE
Insulation class	2
Protection type (IP)	IP65
Electrical connection	
Type of dimming	0-10V

Input voltage AC	220-240V / 50-60Hz V
CASAMBI Products	
Communication type	Bluetooth
Max. transmission power	+4 dBm