Art.-Nr: LFD12001SC-NW
General light, Emergency light Self-contained Universal, SelfControl (SC), 1 h, IP65, Polycarbonate, Light grey



The robust LED wall- and ceiling-mounted luminaire made from fibreglass-reinforced polyester for damp room applications. The external support brackets simplify mounting.

Automatic monitoring of safety luminaire with SelfControl.

CE


More information
www.rp-group.com/en/item/LFD12001SC-NW

TECHNICAL DATA

Luminaire type	General light, Emergency light
Mounting	Universal
Pictograph	No
Illuminant	LED
Housing material	Polycarbonate
Housing color	Light grey
Protection type (IP)	IP65
Impact resistance (IK)	8
Certification	Waste disposal, CE
Insulation class	1
Supply	Self-contained
Monitoring	SelfControl (SC)
Bridging time	1 h
Battery	LiFePO4 3,2 V/3,0 Ah
Operating mode	Non-maintained / maintained
Input voltage AC	230 V
Input frequency	50 / 60 Hz
Power max.	40 W
Power maintained	37 W
Power non-maintained	0,7 W
Ambient temperature maintained mode	-5 °C to 40 °C

Ambient temperature non-maintained mode	-5 °C to 40 °C
Depth	1220 mm
Width	82 mm
Height	97 mm
Weight	1.8
Weight incl. packaging	2.05
Connection cross-section	1.5 mm²
Switching input	Yes
Emergency light blocking	No
Battery connection	Connector
Dimming function	No
Luminous flux mains	4500 lm
Luminous flux emergency	500 lm
EOF	0.11
Customs tariff number	94051140
GTIN	4260659566456

TECHNICAL DRAWING



As of: 15.11.2026 - Subject to technical changes and errors.