



**Art.-Nr: PFW011**  
**Exit sign Self-contained**  
**Wall mounting, 1 h, 24 m, IP65, Polycarbonate, White, Set of**  
**pictograms, Flexiklick**

Robust plastic emergency exit sign or safety luminaire.

Use as an emergency exit sign luminaire for wall mounting.

Or without the use of pictograms as a safety luminaire with the prismatic cover included, preferably for ceiling mounting.

Planning certainty is provided by tool-free, variable use of the pictograms on site. A set of pictograms corresponding to DIN ISO 7010 (arrow to the right, left and down) is supplied as standard. The luminaire is fitted with the innovative flexible plug-in system for rapid use of the right lens. The corridor lens is supplied with every luminaire. A round lens, spotlight lens and beam lens are available as options.



More information  
[www.rp-group.com/en/item/PFW011](http://www.rp-group.com/en/item/PFW011)



## TECHNICAL DATA

|                        |                             |
|------------------------|-----------------------------|
| Luminaire type         | Exit sign                   |
| Mounting               | Wall mounting               |
| Recognition distance   | 24 m                        |
| Pictograph             | Set                         |
| Illuminant             | LED                         |
| Housing material       | Polycarbonate               |
| Housing color          | White                       |
| Protection type (IP)   | IP65                        |
| Impact resistance (IK) | 5                           |
| Certification          | WEEE, CE, D-Sign            |
| Insulation class       | 1                           |
| Supply                 | Self-contained              |
| Monitoring             | ECB                         |
| Bridging time          | 1 h                         |
| Battery                | NIMH 4,8 V/2,0 Ah           |
| Operating mode         | Non-maintained / maintained |



|                                         |                     |
|-----------------------------------------|---------------------|
| Input voltage AC                        | 230 V               |
| Input frequency                         | 50 / 60 Hz          |
| Power max.                              | 6,1 W               |
| Power maintained                        | 4,5 W               |
| Power non-maintained                    | 0,35 W              |
| Ambient temperature maintained mode     | -5 °C to 40 °C      |
| Ambient temperature non-maintained mode | -5 °C to 40 °C      |
| Depth                                   | 370 mm              |
| Width                                   | 105 mm              |
| Height                                  | 152 mm              |
| Weight                                  | 1.07                |
| Weight incl. packaging                  | 1.2                 |
| Connection cross-section                | 2.5 mm <sup>2</sup> |
| Switching input                         | Yes                 |
| Emergency light blocking                | Yes                 |
| Battery connection                      | Connector           |
| Dimming function                        | Yes                 |
| Luminous flux mains                     | 220 lm              |
| Luminous flux emergency                 | 300 lm              |
| Customs tariff number                   | 94056120            |
| GTIN                                    | 4260682144751       |



## TECHNICAL DRAWING



## ACCESSORY LIST

BALL2 - Wire mesh guard



## RELATED PRODUCTS

| Art.-No.          | Image | Monitoring                 | Supply         | Color    | Investment | Automatic log | Maintenance level | Remote maintenance | max. luminaires  | Single luminaire monitoring |
|-------------------|-------|----------------------------|----------------|----------|------------|---------------|-------------------|--------------------|------------------|-----------------------------|
| PFW011-EHE        |       | ECB                        |                | RAL 9003 |            |               |                   |                    |                  |                             |
| PFW011SC          |       | SelfControl (SC)           | Single battery | RAL 9003 | €          | no            | high              | no                 | unlimited        | itself                      |
| PFW011SC-EHE      |       | SelfControl (SC)           | Single battery | RAL 9003 | €          | no            | high              | no                 | unlimited        | itself                      |
| PFW011SC-P        |       | SelfControl (SC)           | Single battery | RAL 9003 | €          | no            | high              | no                 | unlimited        | itself                      |
| PFW011WL          |       | Wireless Professional (WL) | self contained | RAL 9003 | €€         | yes           | low               | yes                | 1,000 per system | central                     |
| PFW011WL-COOLIP54 |       | Wireless Professional (WL) | self contained | RAL 9003 | €€         | yes           | low               | yes                | 1,000 per system | central                     |
| PFW011WL-EHE      |       | Wireless Professional (WL) | self contained | RAL 9003 | €€         | yes           | low               | yes                | 1,000 per system | central                     |
| PFW011WLSE        |       | Wireless Professional (WL) | self contained | RAL 9003 | €€         | yes           | low               | yes                | 1,000 per system | central                     |
| PFW011-COOLIP54   |       | ECB                        |                | RAL 9003 |            |               |                   |                    |                  |                             |
| PFW011SC-COOLIP54 |       | SelfControl (SC)           | Single battery | RAL 9003 | €          | no            | high              | no                 | unlimited        | itself                      |
| PFW411WL          |       | Wireless Professional (WL) | self contained | RAL 9003 | €€         | yes           | low               | yes                | 1,000 per system | central                     |

As of: 23.07.2026 - Subject to technical changes and errors.