



Art.-Nr: PFW011SC-P
Exit sign Self-contained
Wall mounting, 1 h, 24 m, IP65, Polycarbonate, White, Set of
pictograms, Flexiklick

Robust plastic emergency exit sign or safety luminaire.

Use as an emergency exit sign luminaire for wall mounting.

Or without the use of pictograms as a safety luminaire with the prismatic cover included, preferably for ceiling mounting.

Automatic monitoring of safety luminaire with SelfControl. Planning certainty is provided by tool-free, variable use of the pictograms on site. A set of pictograms corresponding to DIN ISO 7010 (arrow to the right, left and down) is supplied as standard. The luminaire is fitted with the innovative flexible plug-in system for rapid use of the right lens. The corridor lens is supplied with every luminaire. A round lens, spotlight lens and beam lens are available as options.



More information

www.rp-group.com/en/item/PFW011SC-P



TECHNICAL DATA


Luminaire type	Exit sign
Mounting	Wall mounting
Recognition distance	24 m
Pictograph	Set
Illuminant	LED
Housing material	Polycarbonate
Housing color	White
Protection type (IP)	IP65
Impact resistance (IK)	5
Certification	WEEE, CE, D-Sign
Insulation class	1
Supply	Self-contained
Monitoring	SelfControl (SC)
Bridging time	1 h
Battery	NIMH 4,8 V/2,0 Ah
Operating mode	Non-maintained / maintained



Input voltage AC	230 V
Input frequency	50 / 60 Hz
Power max.	6,1 W
Power maintained	4,5 W
Power non-maintained	0,35 W
Ambient temperature maintained mode	-5 °C to 40 °C
Ambient temperature non-maintained mode	-5 °C to 40 °C
Depth	150 mm
Width	365 mm
Height	110 mm
Weight	1.07
Weight incl. packaging	1.2
Connection cross-section	2.5 mm ²
Switching input	Yes
Emergency light blocking	Yes
Battery connection	Connector
Dimming function	Yes
Luminous flux mains	220 lm
Luminous flux emergency	300 lm
Customs tariff number	94056120
GTIN	4260682143785



TECHNICAL DRAWING



ACCESSORY LIST

BALL2 - Wire mesh guard



RELATED PRODUCTS

Art.-No.	Image	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote maintenance	max. luminaires	Single luminaire monitoring
PFW011		ECB		RAL 9003						
PFW011-EHE		ECB		RAL 9003						
PFW011SC		SelfControl (SC)	Single battery	RAL 9003	€	no	high	no	unlimited	itself
PFW011SC-EHE		SelfControl (SC)	Single battery	RAL 9003	€	no	high	no	unlimited	itself
PFW011WL		Wireless Professional (WL)	self contained	RAL 9003	€€	yes	low	yes	1,000 per system	central
PFW011WL-COOLIP54		Wireless Professional (WL)	self contained	RAL 9003	€€	yes	low	yes	1,000 per system	central
PFW011WL-EHE		Wireless Professional (WL)	self contained	RAL 9003	€€	yes	low	yes	1,000 per system	central
PFW011WLSE		Wireless Professional (WL)	self contained	RAL 9003	€€	yes	low	yes	1,000 per system	central
PFW011-COOLIP54		ECB		RAL 9003						
PFW011SC-COOLIP54		SelfControl (SC)	Single battery	RAL 9003	€	no	high	no	unlimited	itself
PFW411WL		Wireless Professional (WL)	self contained	RAL 9003	€€	yes	low	yes	1,000 per system	central

As of: 23.07.2026 - Subject to technical changes and errors.