




Art.-Nr: LFD15009-NW
General light, Emergency light Centralised power supply systems
Universal, CPS, IP65, Polycarbonate, Light grey

The robust LED wall- and ceiling-mounted luminaire made from fibreglass-reinforced polyester for damp room applications. The external support brackets simplify mounting.



More information
www.rp-group.com/en/item/LFD15009-NW



TECHNICAL DATA


Luminaire type	General light, Emergency light
Mounting	Universal
Pictograph	No
Illuminant	LED
Housing material	Polycarbonate
Housing color	Light grey
Protection type (IP)	IP65
Impact resistance (IK)	8
Certification	CE, WEEE
Insulation class	1
Supply	Centralised power supply systems
Monitoring	Without monitoring
Bridging time	CPS
Battery	/
Operating mode	Non-maintained / maintained
Input voltage AC	230 V
Input frequency	50 / 60 Hz
Input voltage DC	216 V
Power max.	54 W
Power maintained	54 W
Ambient temperature maintained mode	-5 °C to 40 °C
Ambient temperature non-maintained mode	-5 °C to 40 °C



Depth	1560 mm
Width	82 mm
Height	97 mm
Weight	2.2
Weight incl. packaging	2.55
Connection cross-section	1.5 mm ²
Switching input	Yes
Emergency light blocking	No
Battery connection	No
Dimming function	No
Luminous flux mains	6800 lm
Luminous flux emergency	6800 lm
EOF	1
Customs tariff number	94051140
GTIN	4260682142108



TECHNICAL DRAWING



As of: 24.07.2026 - Subject to technical changes and errors.