



Art.-Nr: KXU011
Exit sign Self-contained
Universal, Without monitoring, 1 h, 30 m, IP40,
Polycarbonate, White

Innovative plastic emergency exit sign luminaire for universal mounting, in a conically tapering housing producing an appealing look. Suited to inscription on one or two sides.



Planning certainty is provided by tool-free, variable use of the pictograms on site. A set of pictograms corresponding to DIN ISO 7010 (arrow to the right, left, up and down) is supplied as standard. Universal mounting includes fitting on the wall and ceiling as well as the option of fitting in the ceiling in conjunction with the mounting frame available.



More information
www.rp-group.com/en/item/KXU011



TECHNICAL DATA

Luminaire type	Exit sign
Mounting	Universal
Recognition distance	30 m
Pictograph	Set
Illuminant	LED
Housing material	Polycarbonate
Housing color	White
Protection type (IP)	IP40
Impact resistance (IK)	≥ 3
Certification	WEEE, CE
Insulation class	2
Supply	Self-contained
Monitoring	Without monitoring
Bridging time	1 h
Battery	NIMH 4,8 V/2,0 Ah
Operating mode	Non-maintained / maintained
Input voltage AC	230 V



Input frequency	50 / 60 Hz
Power max.	6,1 W
Power maintained	4,5 W
Power non-maintained	0,35 W
Ambient temperature maintained mode	-5 °C to 35 °C
Ambient temperature non-maintained mode	-5 °C to 40 °C
Depth	48 mm
Width	332 mm
Height	242 mm
Weight	0.98
Weight incl. packaging	1.09
Connection cross-section	2.5 mm ²
Switching input	Yes
Emergency light blocking	Yes
Battery connection	Connector
Dimming function	Yes
Luminous flux mains	220 lm
Luminous flux emergency	300 lm
Customs tariff number	94056120
GTIN	4260682144638



TECHNICAL DRAWING



ACCESSORY LIST

- KXE-EB -
- AWX001 -
- DSA - Wire suspension
- 2PW-EB - Pendant
- 2DW-EB -
- KXBE -
- NIMHHT4820Q - Battery



RELATED PRODUCTS

Art.-No.	Image	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote maintenance	max. luminaires	Single luminaire monitoring
KXU001SC		SelfControl (SC)	Single battery	RAL 9003	€	no	high	no	unlimited	itself
KXU001WL		Wireless Professional (WL)	Single battery	RAL 9003	€€	yes	low	yes	1,000 per system	central
KXU011SC		SelfControl (SC)	Single battery	RAL 9003	€	no	high	no	unlimited	itself
KXU011SC-W		SelfControl (SC)	Single battery	RAL 9003	€	no	high	no	unlimited	itself

As of: 05.09.2025 - Subject to technical changes and errors.