



Art.-Nr: YMOCA-CASADIMM CASA Trailing Edge Dimmer

Using the CASA Trailing Edge Dimmer allows trailing edge illuminants to be continuously dimmed. Output rating of 150W LED / 200W ohmic (e.g. bulbs). It is controlled wirelessly with the CASAMBI® app. Strain relief and a terminal cover are integrated.



More information

www.rp-group.com/en/item/YMOCA-CASADIMM



TECHNICAL DATA

Dimensions	
Product dimensions Length	143 mm
Product dimensions Width	47 mm
Product dimensions Height	29 mm
Packaging dimensions	
Packaging dimensions Length	162 mm
Packaging dimensions Width	51 mm
Packaging dimensions Height	31 mm
Color	
Color	White
Housing material	
Housing material	Polycarbonate
Certification	
Certification	CE
Insulation class	2
Protection type (IP)	IP20
Housing temperature tc (Max)	
Housing temperature tc (Max)	60 °C
Electrical connection	
Connection cross-section	2,5 mm ²
Temperatures	
Ambient temperature (Min)	-20 °C



Ambient temperature (Max)	+50 °C
CASAMBI Products	
Input voltage AC	230 V
Input frequency	50 Hz
Power (Max)	150 W
Consumption in standby mode	0.5 W
Load types	Capacitive load
Dimming function	TRIAC
Communication type	CASAMBI
Frequency band	2,403 - 2,479 GHz
Max. transmission power	+4 dBm
CASAMBI Repeater	Yes
Protection type (IP)	IP20
Certifications	CE, RoHS

As of: 12.05.2026 - Subject to technical changes and errors.