



**Art.-Nr: AGW009ML**  
**Exit sign Centralised power supply systems**  
**Wall mounting, CPS, 50m, IP40, Zinc die-cast, White,**  
**Piktogram as required**



Modern zinc die-cast emergency exit sign luminaire for surface mounting on the wall and for identifying emergency and escape routes.

It is part of the A series luminaire family, which provides solutions for any mounting and has won the German Design Award for its uniform, straight-line design.

Control and monitoring via central power supply system. The requested pictogram (arrow to the right, left, up or down) is supplied as standard.



More information  
[www.rp-group.com/en/item/AGW009ML](http://www.rp-group.com/en/item/AGW009ML)



## TECHNICAL DATA


|                        |                                  |
|------------------------|----------------------------------|
| Luminaire type         | Exit sign                        |
| Mounting               | Wall mounting                    |
| Recognition distance   | 50m                              |
| Pictograph             | acc. to Specification            |
| Illuminant             | LED                              |
| Housing material       | Zinc die-cast                    |
| Housing color          | White                            |
| Protection type (IP)   | IP40                             |
| Impact resistance (IK) | ≥ 3                              |
| Certification          | WEEE, CE                         |
| Insulation class       | 2                                |
| Supply                 | Centralised power supply systems |
| Monitoring             | Central power supply (ML)        |
| Bridging time          | CPS                              |
| Battery                | /                                |
| Operating mode         | single luminaire switching       |
| Input voltage AC       | 230 V                            |
| Input frequency        | 50 / 60 Hz                       |
| Input voltage DC       | 216 V                            |



|                                         |                     |
|-----------------------------------------|---------------------|
| Power max.                              | 6,1 W               |
| Power maintained                        | 6,1 W               |
| Power non-maintained                    | 1,1 W               |
| Ambient temperature maintained mode     | -5 °C to 40 °C      |
| Ambient temperature non-maintained mode | -5 °C to 40 °C      |
| Depth                                   | 51 mm               |
| Width                                   | 517 mm              |
| Height                                  | 296 mm              |
| Weight                                  | 2.87                |
| Weight incl. packaging                  | 3.52                |
| Connection cross-section                | 2.5 mm <sup>2</sup> |
| Switching input                         | Yes                 |
| Emergency light blocking                | No                  |
| Battery connection                      | No                  |
| Dimming function                        | Yes                 |
| Customs tariff number                   | 94056180            |
| GTIN                                    | 4260659565596       |



## TECHNICAL DRAWING



## RELATED PRODUCTS

| Art.-No.    | Image | Monitoring                | Supply               | Color     | Investment | Automatic log | Maintenance level | Remote maintenance | max. luminaires  | Single luminaire monitoring |
|-------------|-------|---------------------------|----------------------|-----------|------------|---------------|-------------------|--------------------|------------------|-----------------------------|
| AGW009ML-AZ |       | Central power supply (ML) | Central power supply | RAL 7016  | €€€        | Yes           | low               | Yes                | 1,920 per system | central                     |
| AGW009ML-E  |       | Central power supply (ML) | Central power supply | Edelstahl | €€€        | Yes           | low               | Yes                | 1,920 per system | central                     |

As of: 02.09.2026 - Subject to technical changes and errors.