



Art.-Nr: ROPA4201SC-WW
General light, Emergency light Self-contained
Ceiling mounting, SelfControl (SC), 3 h, IP20, Metal, White

LED ceiling panel for general-purpose lighting with integrated safety light function for illuminating escape and emergency routes. The cover is made from PMMA plastic and is therefore UV-resistant, which prevents yellowing.

Automatic monitoring of safety luminaire with SelfControl.



More information

www.rp-group.com/en/item/ROPA4201SC-WW



TECHNICAL DATA

Luminaire type	General light, Emergency light
Mounting	Ceiling mounting
Pictograph	No
Illuminant	LED
Housing material	Metal
Housing color	White
Protection type (IP)	IP20
Impact resistance (IK)	≥ 3
Certification	WEEE, CE
Insulation class	2
Supply	Self-contained
Monitoring	SelfControl (SC)
Bridging time	3 h
Battery	/
Operating mode	Non-maintained / maintained
Input voltage AC	230 V
Input frequency	50 Hz
Input voltage DC	- V
Power max.	33 W



Power maintained	33 W
Power non-maintained	2 W
Ambient temperature maintained mode	0 °C to 40 °C
Ambient temperature non-maintained mode	0 °C to 40 °C
Depth	620 mm
Width	620 mm
Height	10 mm
Weight	3.7
Weight incl. packaging	4.1
Connection cross-section	1.5 mm ²
Switching input	Yes
Emergency light blocking	No
Battery connection	Clip
Dimming function	No
Luminous flux mains	4000 lm
Luminous flux emergency	600 lm
EOF	0.15
Customs tariff number	94056120
GTIN	4260682142412

As of: 04.07.2026 - Subject to technical changes and errors.