



**Art.-Nr: QCW009ML-BM**  
**General light, Emergency light Centralised power supply systems**  
**Universal, CPS, IP54, Zinc die-cast, White, HF motion detector**

Round zinc die-cast LED luminaire, as combined safety luminaire in a timeless design.

Alongside the general-purpose lighting, it also includes an integrated safety light function. When mounting, the emergency light LED can be swung out without the need for tools, to perfectly illuminate the escape and emergency routes when mounted on a wall, for example.

Control and monitoring via central power supply system. The integrated motion detector (BM) reliably detects movements and automatically turns on the light in mains operation.



More information

[www.rp-group.com/en/item/QCW009ML-BM](http://www.rp-group.com/en/item/QCW009ML-BM)



## TECHNICAL DATA

|                        |                                  |
|------------------------|----------------------------------|
| Luminaire type         | General light, Emergency light   |
| Mounting               | Universal                        |
| Pictograph             | No                               |
| Illuminant             | LED                              |
| Housing material       | Zinc die-cast                    |
| Housing color          | White                            |
| Protection type (IP)   | IP54                             |
| Impact resistance (IK) | 10                               |
| Certification          | WEEE, CE, D-Sign                 |
| Insulation class       | 1                                |
| Supply                 | Centralised power supply systems |
| Monitoring             | Central power supply (ML)        |
| Bridging time          | CPS                              |
| Battery                | /                                |
| Operating mode         | Permanent circuit                |
| Input voltage AC       | 230 V                            |
| Input frequency        | 50 Hz                            |




|                                         |                     |
|-----------------------------------------|---------------------|
| Input voltage DC                        | 216 V               |
| Power max.                              | 19,5 W              |
| Power maintained                        | 17,5 W              |
| Power non-maintained                    | 2 W                 |
| Ambient temperature maintained mode     | -5 °C to 40 °C      |
| Ambient temperature non-maintained mode | -5 °C to 40 °C      |
| Height                                  | 106 mm              |
| Diameter                                | 363 mm              |
| Weight                                  | 2.59                |
| Weight incl. packaging                  | 2.92                |
| Connection cross-section                | 1.5 mm <sup>2</sup> |
| Switching input                         | No                  |
| Emergency light blocking                | No                  |
| Battery connection                      | No                  |
| Dimming function                        | No                  |
| Luminous flux mains                     | 1600 lm             |
| Luminous flux emergency                 | 1600 lm             |
| EOF                                     | 1                   |
| Customs tariff number                   | 94056180            |
| GTIN                                    | 4260682146229       |




TECHNICAL DRAWING

QCW



QCW



As of: 25.08.2026 - Subject to technical changes and errors.