RP GROUP
SOLUTIONS IN SAFETY + LIGHTING

Art.-Nr: ILDL423SC-SW-3P
Emergency light Self-contained Track system, SelfControl (SC), 3 h, IP40, Polycarbonate, Black, Flexiklick round & corridor, 3-Phase railadapter



The LED safety luminaire IL with its unobtrusive design is a real all-rounder. it is equipped for virtually all requirements and always provides the right solution. Since the status LED is fitted in the lens, the harmony of the discreet housing is not interrupted.

Automatic monitoring of safety luminaire with SelfControl. The innovative integrated lens holder with a rapid fitting fixture permits the flexible use of various lens types. Using the right lens allows the distribution of light to be matched perfectly to the application and simplifies illumination which satisfies all relevant standards. A round lens and corridor lens are supplied with every luminaire, allowing it to be adapted perfectly to the respective mounting situation. Other lenses, such as a spotlight lens, beam lens or H lens, are available as options. The pre-mounted 3-phase adapter allows for tool-free installation in popular 3-phase tracks, such as Nordic Aluminium GLOBAL pro (previously NOKIA) XTS, XTTS and XTSC.

CE

5 JAHRE 5 YEARS GARANTIE WARRANTY


More information
www.rp-group.com/en/item/ILDL423SC-SW-3P

TECHNICAL DATA

Luminaire type	Emergency light
Mounting	Track system
Illuminant	LED
Housing material	Polycarbonate
Housing color	Black
Protection type (IP)	IP40
Impact resistance (IK)	≥ 3
Certification	Waste disposal, CE, 5 Years waranty
Insulation class	2
Supply	Self-contained
Monitoring	SelfControl (SC)
Bridging time	3 h
Battery	LiFePO4 3,2 V/3,3 Ah
Operating mode	Non-maintained / maintained

Input voltage AC	230 V
Input frequency	50 / 60 Hz
Power max.	3 W
Power maintained	1,9 W
Power non-maintained	0,2 W
Ambient temperature maintained mode	-5 °C to 40 °C
Ambient temperature non-maintained mode	-5 °C to 40 °C
Height	36 mm
Diameter	100 mm
Weight	0.19
Weight incl. packaging	0.23
Connection cross-section	2.5 mm²
Switching input	Yes
Emergency light blocking	No
Battery connection	Connector
Dimming function	Yes
Luminous flux mains	130 lm
Luminous flux emergency	250 lm
Customs tariff number	94056120
GTIN	4260682155627

TECHNICAL DRAWING



ACCESSORY LIST

ILD-APA-02 - IL surface-mounted adapter

IL-IK10-AZ - High protection surface-mounted housing for ILD luminaires: IP 65 & IK 10

IL-IK10-W - Robust ILD modular system IP 65 / IK 10 – ball-impact resistant

ILDE - Mounting frame

ILB1 - IL top part

ILB2 - IL top part

BALLPLX-ILD - Ball impact-resistant protective cover (PMMA) transparent for lights -

IL-IP65-K - Surface-mounted housing

LSYS-B4 - Precision beam lens for accent lighting of safety devices





LSYS-F4 - Precise corridor lens for emergency exit and corridor lighting

LSYS-R4 - High-performance round lens for uniform emergency light distribution in open areas

LSYS-S4 - Precision spot lens for emergency lighting in large areas and high ceilings

LSYS-WD4 - Wall-down lens for precise corridor lighting and safety lights

RELATED PRODUCTS

Art.-No.	Image	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote maintenance	max. luminaires	Single luminaire monitoring
ILDL423SC		SelfControl (SC)	Single battery	RAL 9003	€	no	high	no	unlimited	itself
ILDL423SC-SW		SelfControl (SC)	Single battery	RAL 9005	€	no	high	no	unlimited	itself
ILDL423WL		Wireless Professional (WL)	self contained	RAL 9003	€€	yes	low	yes	1,000 per system	central
ILDL423WL-SW		Wireless Professional (WL)	self contained	RAL 9005	€€	yes	low	yes	1,000 per system	central
ILDL423SC-3P		SelfControl (SC)	Single battery	RAL 9003	€	no	high	no	unlimited	itself
ILDL423WL-3P		Wireless Professional (WL)	self contained	RAL 9003	€€	yes	low	yes	1,000 per system	central
ILDL423WL-SW-3P		Wireless Professional (WL)	self contained	RAL 9005	€€	yes	low	yes	1,000 per system	central

As of: 22.11.2026 - Subject to technical changes and errors.