



Art.-Nr: WFXW418WL
Exit sign Self-contained
Wall mounting, 8 h, 30 m, IP65, Polycarbonate, White,
Piktogram as required

Modern exit sign wall luminaire in a square format.

For marking escape and rescue routes. Optionally, the light can be used to mark other adjacent rooms, such as showers, restrooms, or changing rooms.

The easy-to-install bayonet lock allows for safe opening and closing of the light. It also ensures a high protection rating, making the light versatile and flexible.

Wireless central control and monitoring for large installations of up to 50,000 luminaires with Wireless Professional. The requested pictogram (arrow to the right, left, up or down) is supplied as standard.



More information

www.rp-group.com/en/item/WFXW418WL



TECHNICAL DATA


Luminaire type	Exit sign
Mounting	Wall mounting
Recognition distance	30 m
Pictograph	acc. to Specification
Illuminant	LED
Housing material	Polycarbonate
Housing color	White
Protection type (IP)	IP65
Impact resistance (IK)	4
Certification	WEEE, CE, 5 years warranty, D-Sign
Insulation class	2
Supply	Self-contained
Monitoring	Wireless Professional (WL)
Bridging time	8 h
Battery	LiFePO4 3,2 V/3,3 Ah
Operating mode	Non-maintained / maintained
Input voltage AC	230 V
Input frequency	50 Hz




Power max.	7,5 W
Power maintained	5,7 W
Power non-maintained	0,8 W
Ambient temperature maintained mode	0 °C to 40 °C
Ambient temperature non-maintained mode	0 °C to 40 °C
Depth	300 mm
Width	300 mm
Height	110 mm
Weight	1.45
Weight incl. packaging	1.7
Connection cross-section	2.5 mm ²
Switching input	Yes
Emergency light blocking	Yes
Battery connection	Connector
Dimming function	Yes
Luminous flux mains	250 lm
Luminous flux emergency	245 lm
Customs tariff number	94056180
GTIN	4260682158451



TECHNICAL DRAWING





ACCESSORY LIST

LFP3233-SET-2AKKU - Battery

As of: 24.08.2026 - Subject to technical changes and errors.