




Art.-Nr: LFD15003SC-NW-BM
General light, Emergency light
Universal, 8 h, IP65, Polycarbonate, Light grey

The robust LED wall- and ceiling-mounted luminaire made from fibreglass-reinforced polyester for damp room applications. The external support brackets simplify mounting.

Automatic monitoring of safety luminaire with SelfControl.



More information

www.rp-group.com/en/item/LFD15003SC-NW-BM




TECHNICAL DATA

Luminaire type	General light, Emergency light
Mounting	Universal
Pictograph	No
Housing material	Polycarbonate
Housing color	Light grey
Protection type (IP)	IP65
Impact resistance (IK)	8
Certification	CE, WEEE
Insulation class	1
Monitoring	SelfControl (SC)
Bridging time	8 h
Battery	LiFePO4 3,2 V/4,5 Ah
Power maintained	54 W
Ambient temperature maintained mode	-5 °C to 40 °C
Ambient temperature non-maintained mode	-5 °C to 40 °C
Depth	1560 mm
Width	82 mm
Height	97 mm
Weight	2.33
Weight incl. packaging	2.68
Luminous flux mains	6500 lm
EOF	N/A



Customs tariff number	94051140
GTIN	4262483025970

TECHNICAL DRAWING



As of: 24.07.2026 - Subject to technical changes and errors.