



**Art.-Nr: KAXU408SC**  
**Exit sign Self-contained**  
**Universal, 8 h, 30 m, IP65, Polycarbonate, White, Set of**  
**pictograms, Universal mounting**

Plastic emergency exit sign luminaire for universal mounting. The cuboid plastic housing is discreetly reduced to the essentials. The high level of protection permits use in damp rooms or highly contaminated environments.

Automatic monitoring of safety luminaire with SelfControl. Display edge luminaire with integrated light distribution for even pictogram illumination. Suited to inscription on one or two sides. Planning certainty is provided by tool-free, variable use of the pictograms on site. A set of pictograms corresponding to DIN ISO 7010 (arrow to the right, left, up and down) is supplied as standard. Universal mounting includes the option of mounting the luminaire either on the wall or ceiling.



More information  
[www.rp-group.com/en/item/KAXU408SC](http://www.rp-group.com/en/item/KAXU408SC)



## TECHNICAL DATA


|                        |                             |
|------------------------|-----------------------------|
| Luminaire type         | Exit sign                   |
| Mounting               | Universal                   |
| Recognition distance   | 30 m                        |
| Pictograph             | Set                         |
| Illuminant             | LED                         |
| Housing material       | Polycarbonate               |
| Housing color          | White                       |
| Protection type (IP)   | IP65                        |
| Impact resistance (IK) | 7                           |
| Certification          | WEEE, CE, 5 years warranty  |
| Insulation class       | 2                           |
| Supply                 | Self-contained              |
| Monitoring             | SelfControl (SC)            |
| Bridging time          | 8 h                         |
| Battery                | LiFePO4 3,2 V/1,2 Ah        |
| Operating mode         | Non-maintained / maintained |
| Input voltage AC       | 180 V - 230 V               |



|                                         |                     |
|-----------------------------------------|---------------------|
| Input frequency                         | 50 Hz               |
| Power max.                              | 2,6 W               |
| Power maintained                        | 1,7 W               |
| Power non-maintained                    | 0,9 W               |
| Ambient temperature maintained mode     | -5 °C to 40 °C      |
| Ambient temperature non-maintained mode | -5 °C to 40 °C      |
| Depth                                   | 326 mm              |
| Width                                   | 50 mm               |
| Height                                  | 248 mm              |
| Weight                                  | 0.12                |
| Weight incl. packaging                  | 0.32                |
| Connection cross-section                | 2,5 mm <sup>2</sup> |
| Switching input                         | Yes                 |
| Emergency light blocking                | No                  |
| Battery connection                      | Connector           |
| Dimming function                        | No                  |
| Customs tariff number                   | 94056120            |
| GTIN                                    | 4260766551581       |



## TECHNICAL DRAWING



As of: 25.08.2026 - Subject to technical changes and errors.