RP GROUP
SOLUTIONS IN SAFETY + LIGHTING

Art.-Nr: WAF423WL
Emergency light Self-contained Wall mounting, Wireless Professional (WL), 3 h, IP20, Zinc die-cast, White



High-grade zinc die-cast safety luminaire for surface mounting on the wall.

The radiating characteristics run parallel to the wall to help perfectly illuminate escape and emergency routes.

Wireless central control and monitoring for large installations of up to 50,000 luminaires with Wireless Professional.

CE

5 JAHRE 5 YEARS GARANTIE WARRANTY

More information
www.rp-group.com/en/item/WAF423WL


TECHNICAL DATA

Luminaire type	Emergency light
Mounting	Wall mounting
Pictograph	No
Illuminant	LED
Housing material	Zinc die-cast
Housing color	White
Protection type (IP)	IP20
Impact resistance (IK)	4
Certification	Waste disposal, CE, 5 Years waranty
Insulation class	2
Supply	Self-contained
Monitoring	Wireless Professional (WL)
Bridging time	3 h
Battery	LiFePO4 3,2 V/1,2 Ah
Operating mode	Non-maintained / maintained
Input voltage AC	230 V
Input frequency	50 Hz
Power max.	5,1 W
Power maintained	3,9 W
Power non-maintained	0,8 W

Ambient temperature maintained mode	-5 °C to 35 °C
Ambient temperature non-maintained mode	-5 °C to 40 °C
Depth	193 mm
Width	53 mm
Height	115 mm
Weight	0.11
Weight incl. packaging	0.14
Connection cross-section	2.5 mm²
Switching input	Yes
Emergency light blocking	Yes
Battery connection	Connector
Dimming function	Yes
Luminous flux mains	420 lm
Luminous flux emergency	315 lm
Customs tariff number	94056180
GTIN	4260766551918

RP GROUP
SOLUTIONS IN SAFETY + LIGHTING

TECHNICAL DRAWING



ACCESSORY LIST

LFPN3212-SET-2AKKU - Battery

As of: 11.11.2026 - Subject to technical changes and errors.