



Art.-Nr: PFD411WL
Exit sign Self-contained
Surface mounting, Wireless Professional (WL), 1 h, 24 m,
IP65, Polycarbonate, White

Trapezoid, plastic emergency exit sign luminaire for fitting on the ceiling for inscription on one or two sides with self-adhesive pictogram.

Wireless central control and monitoring for large installations of up to 50,000 luminaires with Wireless Professional. Planning certainty is provided by tool-free, variable use of the pictograms on site. A set of pictograms corresponding to DIN ISO 7010 (arrow to the right, left and down) is supplied as standard.



More information
www.rp-group.com/en/item/PFD411WL



TECHNICAL DATA


Luminaire type	Exit sign
Mounting	Surface mounting
Recognition distance	24 m
Pictograph	Set
Illuminant	LED
Housing material	Polycarbonate
Housing color	White
Protection type (IP)	IP65
Impact resistance (IK)	6
Certification	WEEE, CE, 5 years warranty
Insulation class	1
Supply	Self-contained
Monitoring	Wireless Professional (WL)
Bridging time	1 h
Battery	LiFePO4 3,2 V/1,2 Ah
Operating mode	Non-maintained / maintained
Input voltage AC	230 V
Input frequency	50 Hz
Power max.	5,3 W
Power maintained	4,3 W



Power non-maintained	0,7 W
Ambient temperature maintained mode	-5 °C to 40 °C
Ambient temperature non-maintained mode	-5 °C to 40 °C
Depth	152 mm
Width	370 mm
Height	195 mm
Weight	0.96
Weight incl. packaging	1.09
Connection cross-section	2.5 mm ²
Switching input	Yes
Emergency light blocking	Yes
Battery connection	Connector
Dimming function	Yes
Luminous flux mains	305 lm
Luminous flux emergency	335 lm
Customs tariff number	94056120
GTIN	4260766552045



TECHNICAL DRAWING



ACCESSORY LIST

2PW-EB - Pendant

2DW-EB - Pre-assembled designer pendant pair with fixed canopy, 4-core, white

DSA - Wire suspension

PFER - High-quality metal mounting frame for PF series emergency lights - 410 x 190 mm

LFPN3212-SET-2AKKU - Battery



RELATED PRODUCTS

Art.-No.	Image	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote maintenance	max. luminaires	Single luminaire monitoring
PFD011		ECB		RAL 9003						
PFD011-COOLIP54		ECB		RAL 9003						
PFD011-EHE		ECB		RAL 9003						
PFD011SC		SelfControl (SC)	Single battery	RAL 9003	€	no	high	no	unlimited	itself
PFD011SC-COOLIP54		SelfControl (SC)	Single battery	RAL 9003	€	no	high	no	unlimited	itself
PFD011SC-EHE		SelfControl (SC)	Single battery	RAL 9003	€	no	high	no	unlimited	itself

As of: 15.07.2026 - Subject to technical changes and errors.