



Art.-Nr: KXU013-W
Exit sign Self-contained
Universal, Without monitoring, 1 h, 30 m, IP40,
Polycarbonate, White

Innovative plastic emergency exit sign luminaire for universal mounting, in a conically tapering housing producing an appealing look. Suited to inscription on one or two sides.



Planning certainty is provided by tool-free, variable use of the pictograms on site. A set of pictograms corresponding to DIN ISO 7010 (arrow to the right, left, up and down) is supplied as standard. Universal mounting includes fitting on the wall and ceiling as well as the option of fitting in the ceiling in conjunction with the mounting frame available.



More information
www.rp-group.com/en/item/KXU013-W



TECHNICAL DATA

Luminaire type	Exit sign
Mounting	Universal
Recognition distance	30 m
Pictograph	Set
Illuminant	LED
Housing material	Polycarbonate
Housing color	White
Protection type (IP)	IP40
Impact resistance (IK)	≥ 3
Certification	WEEE, CE
Insulation class	2
Supply	Self-contained
Monitoring	Without monitoring
Bridging time	1 h
Battery	NIMH 12 V/0,8 Ah
Operating mode	Non-maintained / maintained
Input voltage AC	230 V



Input frequency	50 / 60 Hz
Input voltage DC	- V
Power max.	6,5 W
Power maintained	6,5 W
Power non-maintained	2,66 W
Ambient temperature maintained mode	-5 °C to 35 °C
Ambient temperature non-maintained mode	-5 °C to 40 °C
Depth	48 mm
Width	332 mm
Height	242 mm
Weight	1.16
Weight incl. packaging	1.27
Connection cross-section	2.5 mm ²
Switching input	Yes
Emergency light blocking	No
Battery connection	Clip
Dimming function	Yes
Luminous flux mains	150 lm
Luminous flux emergency	150 lm
Customs tariff number	94056120
GTIN	4260659567774



Technical drawings of the 'EXIT' sign, showing front and side views with dimensions.

Front View (Top):

- Overall width: 332
- Overall height: 242
- Top section height: 72
- Bottom section height: 170
- Bottom section width: 312
- Icons: A downward arrow and a running figure.

Side View (Top):


- Width: 48
- Height: 10

Front View (Bottom):

- Overall width: 332
- Overall height: 242
- Top section height: 72
- Bottom section height: 170
- Bottom section width: 312
- Icons: A downward arrow and a running figure.

Side View (Bottom):

- Width: 48
- Height: 10



KXE-EB -
AWX001 -
DSA - Wire suspension
2PW-EB - Pendant
2DW-EB -
KXBE -
NIMHHT4820Q - Battery

www.rp-group.com