
Art.-Nr: KBU411SC
Exit sign, Emergency light Self-contained Universal, SelfControl (SC), 1 h, 14 m, 22 m, 30 m, IP65, Polycarbonate, White, Universal mounting



Flexible plastic safety luminaire for universal mounting, which can be extended to become an emergency exit sign luminaire. The cuboid plastic housing is discreetly reduced to the essentials.

Because of the modular system, the luminaire can be converted into an emergency exit sign luminaire without any tools and without having to be disassembled. The panes for fitting the pictograms are available separately.

Automatic monitoring of safety luminaire with SelfControl. Universal mounting includes fitting on the wall and ceiling as well as the option of fitting in the ceiling in conjunction with the mounting frame available.


More information
www.rp-group.com/en/item/KBU411SC


TECHNICAL DATA

Luminaire type	Exit sign, Emergency light
Mounting	Universal
Recognition distance	14 m, 22 m, 30 m
Pictograph	acc. to Specification
Illuminant	LED
Housing material	Polycarbonate
Housing color	White
Protection type (IP)	IP65
Impact resistance (IK)	5
Certification	Waste disposal, CE, 5 Years waranty, D-sign
Insulation class	2
Supply	Self-contained
Monitoring	SelfControl (SC)
Bridging time	1 h
Battery	LiFePO4 3,2 V/1,6 Ah
Operating mode	Non-maintained / maintained
Input voltage AC	230 V - 240 V

Input frequency	50 Hz
Power max.	4,2 W
Power maintained	3,3 W
Power non-maintained	0,9 W
Ambient temperature maintained mode	-5 °C to 35 °C
Ambient temperature non-maintained mode	-5 °C to 40 °C
Depth	326 mm
Width	50 mm
Height	50 mm
Weight	0.42
Weight incl. packaging	0.47
Connection cross-section	2,5 mm²
Switching input	Yes
Emergency light blocking	No
Battery connection	Connector
Dimming function	No
Luminous flux mains	190 lm
Luminous flux emergency	190 lm
EOF	1
Customs tariff number	94056120
GTIN	4260766553370

TECHNICAL DRAWING





ACCESSORY LIST

KBK - KBU emergency light: Modular escape route light with variable visibility

KBM - KBU emergency light: Flexible escape route lighting with tool-free lens replacement

KBG - KBU emergency light – tool-free adjustment for variable viewing distances

AWX001 - AWX wall bracket for emergency lights - 90° flag mounting

KBE - Mounting frame

BALLPLX-KBE - Ball impact-resistant protective cover (PMMA) transparent for lights - KB in recessed frame

BALLPLX-KBS - Ball impact-resistant protective cover (PMMA) transparent for lights - KB incl. edge and pictogram

BALLPLX-KBU - Ball impact-resistant protective cover (PMMA) transparent for lights - KBU safety luminaire

2PW-EB - Pendant

2DW-EB - Pre-assembled designer pendant pair with fixed canopy, 4-core, white

KBBE - Flush-mounted box

DSA - Wire suspension