



Art.-Nr: MMD403SC-AZ
Exit sign Self-contained
Surface mounting, 3 h, 21 m, IP40, Zinc die-cast, Anthracite,
Set of pictograms

Slim, high-quality, zinc die-cast emergency exit sign luminaire with a modern design for ceiling mounting. Suited to inscription on one or two sides.

Automatic monitoring of safety luminaire with SelfControl. Planning certainty is provided by tool-free, variable use of the pictograms on site. A set of pictograms corresponding to DIN ISO 7010 (arrow to the right, left, up and down) is supplied as standard.



More information

www.rp-group.com/en/item/MMD403SC-AZ



TECHNICAL DATA

| | |
|------------------------|-----------------------------|
| Luminaire type | Exit sign |
| Mounting | Surface mounting |
| Recognition distance | 21 m |
| Pictograph | Set |
| Illuminant | LED |
| Housing material | Zinc die-cast |
| Housing color | Anthracite |
| Protection type (IP) | IP40 |
| Impact resistance (IK) | ≥ 3 |
| Certification | WEEE, CE, 5 years warranty |
| Insulation class | 1 |
| Supply | Self-contained |
| Monitoring | SelfControl (SC) |
| Bridging time | 3 h |
| Battery | LiFePO4 3,2 V/1,2 Ah |
| Operating mode | Non-maintained / maintained |
| Input voltage AC | 180 V - 230 V |
| Input frequency | 50 Hz |
| Power max. | 4,2 W |
| Power maintained | 3,3 W |



| | |
|---|---------------------|
| Power non-maintained | 0,9 W |
| Ambient temperature maintained mode | -5 °C to 40 °C |
| Ambient temperature non-maintained mode | -5 °C to 40 °C |
| Depth | 46 mm |
| Width | 236 mm |
| Height | 155 mm |
| Weight | 0.11 |
| Weight incl. packaging | 0.23 |
| Connection cross-section | 2,5 mm ² |
| Switching input | Yes |
| Emergency light blocking | No |
| Battery connection | Connector |
| Dimming function | No |
| Customs tariff number | 94056180 |
| GTIN | 4260766556562 |

ACCESSORY LIST

LFPN3212-SET-2AKKU - Battery

As of: 04.07.2026 - Subject to technical changes and errors.