RP GROUP
SOLUTIONS IN SAFETY + LIGHTING

Art.-Nr: WGD411SC
Exit sign Self-contained
Surface mounting, SelfControl (SC), 1 h, 46 m, IP20, Metal, White, printed pictograms



Square emergency exit sign cube luminaire for identifying escape and emergency routes. It can be mounted straight onto the ceiling or suspended using the appropriate accessories.

The cube shape means that this plastic luminaire is easily recognisable from four sides. Ideal for use where routes intersect, e.g. in large stores with aisles.

Automatic monitoring of safety luminaire with SelfControl. Planning certainty is provided by printed pictograms, determined on the basis of logic. The pictograms used correspond to DIN ISO 7010 (arrow to the right, left and down).

CE

5 JAHRE 5 YEARS GARANTIE WARRANTY

More information
www.rp-group.com/en/item/WGD411SC

TECHNICAL DATA


Luminaire type	Exit sign
Mounting	Surface mounting
Recognition distance	46 m
Pictograph	Set
Illuminant	LED
Housing material	Metal
Housing color	White
Protection type (IP)	IP20
Impact resistance (IK)	≥ 3
Certification	Waste disposal, CE, 5 Years waranty
Insulation class	1
Supply	Self-contained
Monitoring	SelfControl (SC)
Bridging time	1 h
Battery	LiFePO4 3,2 V/1,6 Ah
Operating mode	Non-maintained / maintained
Input voltage AC	180 V - 250 V
Input frequency	50 Hz

Power max.	6,4 W
Power maintained	5,6 W
Power non-maintained	2 W
Ambient temperature maintained mode	-5 °C to 40 °C
Ambient temperature non-maintained mode	-5 °C to 40 °C
Depth	237 mm
Width	237 mm
Height	237 mm
Weight	1.23
Weight incl. packaging	1.37
Connection cross-section	2,5 mm²
Switching input	Yes
Emergency light blocking	No
Battery connection	Connector
Dimming function	No
Luminous flux mains	470 lm
Luminous flux emergency	470 lm
Customs tariff number	94056120
GTIN	4260766556807


RP GROUP
SOLUTIONS IN SAFETY + LIGHTING

TECHNICAL DRAWING



231
231


25
138
25
25
70
ø 5
ø 20
ø 10
188
138
24
24
70
25
69
24
24
69
186


WK


25
180
25
25
90
ø 5
ø 20
ø 10
230
180
25
25
90
25
90
25
25
90
230


WG


45
402
45
45
220
ø 5
ø 20
ø 10
492
402
26
26
220
45
220
26
26
220
492

WX



WK WG WX



ACCESSORY LIST

LFP3216-SET-2AKKU - Battery

As of: 14.11.2026 - Subject to technical changes and errors.