
RP GROUP
SOLUTIONS IN SAFETY + LIGHTING

Art.-Nr: WKD413SC
Exit sign Self-contained
Surface mounting, SelfControl (SC), 3 h, 36 m, IP20, Metal, White, printed pictograms



Square emergency exit sign cube luminaire for identifying escape and emergency routes. It can be mounted straight onto the ceiling or suspended using the appropriate accessories.

The cube shape means that this plastic luminaire is easily recognisable from four sides. Ideal for use where routes intersect, e.g. in large stores with aisles.

Automatic monitoring of safety luminaire with SelfControl. Planning certainty is provided by printed pictograms, determined on the basis of logic. The pictograms used correspond to DIN ISO 7010 (arrow to the right, left and down).

CE

5 JAHRE 5 YEARS GARANTIE WARRANTY

More information
www.rp-group.com/en/item/WKD413SC


TECHNICAL DATA


Luminaire type	Exit sign
Mounting	Surface mounting
Recognition distance	36 m
Pictograph	Set
Illuminant	LED
Housing material	Metal
Housing color	White
Protection type (IP)	IP20
Impact resistance (IK)	≥ 3
Certification	Waste disposal, CE, 5 Years waranty
Insulation class	1
Supply	Self-contained
Monitoring	SelfControl (SC)
Bridging time	3 h
Battery	LiFePO4 3,2 V/3,3 Ah
Operating mode	Non-maintained / maintained
Input voltage AC	180 V - 250 V
Input frequency	50 Hz

Power max.	8,2 W
Power maintained	7 W
Power non-maintained	2 W
Ambient temperature maintained mode	-5 °C to 40 °C
Ambient temperature non-maintained mode	-5 °C to 40 °C
Depth	195 mm
Width	195 mm
Height	195 mm
Weight	0.87
Weight incl. packaging	1.01
Connection cross-section	2,5 mm²
Switching input	Yes
Emergency light blocking	No
Battery connection	Connector
Dimming function	No
Luminous flux mains	470 lm
Luminous flux emergency	470 lm
Customs tariff number	94056120
GTIN	4260766556883


RP GROUP
SOLUTIONS IN SAFETY + LIGHTING

TECHNICAL DRAWING







WK




WG



WX


25
138
25
25
70
ø 5
ø 20
ø 10
24
24
70
25
188
138
69
24
24
69
186
WK
25
180
25
25
90
ø 5
ø 20
ø 10
25
25
90
25
230
180
90
25
25
90
230
WG
45
402
45
45
220
ø 5
ø 20
ø 10
26
26
220
45
492
402
220
26
26
220
492
WX


195
195

ACCESSORY LIST

LFP3233-SET-2AKKU - Battery

As of: 14.11.2026 - Subject to technical changes and errors.