



**Art.-Nr: KWID413SC-COOLIP54**

**Exit sign Self-contained**

**Surface mounting, 3 h, 16 m, IP65, Polycarbonate, White, Set of pictograms**

Classic, robust, plastic, beam-like emergency exit sign luminaire with a high level of protection and self-adhesive pictogram for versatile use.

Intended for ceiling mounting when used as an emergency exit sign luminaire. Without the use of pictograms, it can be used as a safety luminaire, preferably for ceiling mounting.

Automatic monitoring of safety luminaire with SelfControl. Planning certainty is provided by tool-free, variable use of the pictograms on site. A set of pictograms corresponding to DIN ISO 7010 (arrow to the right, left, up and down) is supplied as standard.



More information

[www.rp-group.com/en/item/KWID413SC-COOLIP54](http://www.rp-group.com/en/item/KWID413SC-COOLIP54)



**TECHNICAL DATA**

|                        |                             |
|------------------------|-----------------------------|
| Luminaire type         | Exit sign                   |
| Mounting               | Surface mounting            |
| Recognition distance   | 16 m                        |
| Pictograph             | Set                         |
| Illuminant             | LED                         |
| Housing material       | Polycarbonate               |
| Housing color          | White                       |
| Protection type (IP)   | IP65                        |
| Impact resistance (IK) | 6                           |
| Certification          | WEEE, CE, 5 years warranty  |
| Insulation class       | 2                           |
| Supply                 | Self-contained              |
| Monitoring             | SelfControl (SC)            |
| Bridging time          | 3 h                         |
| Battery                | LiFePO4 3,2 V/1,6 Ah        |
| Operating mode         | Non-maintained / maintained |
| Input voltage AC       | 180 V - 230 V               |



|   |                     |
|---|---------------------|
| Input frequency                         | 50 Hz               |
| Power max.                              | 4,2 W               |
| Power maintained                        | 3,3 W               |
| Power non-maintained                    | 0,4 W               |
| Ambient temperature maintained mode     | -5 °C to 40 °C      |
| Ambient temperature non-maintained mode | -5 °C to 40 °C      |
| Depth                                   | 93 mm               |
| Width                                   | 390 mm              |
| Height                                  | 139 mm              |
| Weight                                  | 0.82                |
| Weight incl. packaging                  | 0.92                |
| Connection cross-section                | 2,5 mm <sup>2</sup> |
| Switching input                         | Yes                 |
| Emergency light blocking                | No                  |
| Battery connection                      | Connector           |
| Dimming function                        | No                  |
| Luminous flux mains                     | 190 lm              |
| Luminous flux emergency                 | 190 lm              |
| Customs tariff number                   | 94056120            |
| GTIN                                    | 4260766556364       |



## TECHNICAL DRAWING



## ACCESSORY LIST

BKW - Robust steel protective grille for emergency lighting

LFP3216-SET-2AKKU - Battery

As of: 04.07.2026 - Subject to technical changes and errors.