



Art.-Nr: YMOCA-DIMM-MINI CASA DIMM Mini

NEW PRODUCT!

The CASA DIMM Mini has been developed especially for flush-mounted installation and controls luminaires/drivers capable of trailing edge dimming. Output rating of 200W LED. It is controlled wirelessly with the CASAMBI® app.



More information

www.rp-group.com/en/item/YMOCA-DIMM-MINI



TECHNICAL DATA

Dimensions	
Product dimensions Length	50 mm
Product dimensions Width	48 mm
Product dimensions Height	21.6 mm
Packaging dimensions	
Packaging dimensions Length	60 mm
Packaging dimensions Width	60 mm
Packaging dimensions Height	34 mm
Weight incl. packaging	0.05 kg
Color	
Color	White
Housing material	
Housing material	Polycarbonate
Storage temperature range	
Storage temperature range (Min)	-25 °C
Storage temperature range (Max)	+75 °C
Housing temperature tc (Max)	
Housing temperature tc (Max)	70 °C



Electrical connection	
Connection cross-section	1.5 mm ²
Temperatures	
Ambient temperature (Min)	-20 °C
Ambient temperature (Max)	+50 °C
CASAMBI Products	
Input voltage AC	230 V
Input frequency	50 Hz
Power (Max)	200 W
Consumption in standby mode	0,5 W
Load types	Capacitive load
Dimming function	TRIAC
Communication type	CASAMBI
Frequency band	2,403 - 2,479 GHz
Max. transmission power	+4 dBm
CASAMBI Repeater	Yes
Protection type (IP)	IP20
Certifications	CE, RoHS

As of: 12.05.2026 - Subject to technical changes and errors.