
RP GROUP
SOLUTIONS IN SAFETY + LIGHTING

Art.-Nr: WKD418WL
Exit sign Self-contained
Surface mounting, Wireless Professional (WL), 8 h, 36 m, IP20, Metal, White, printed pictograms



Square emergency exit sign cube luminaire for identifying escape and emergency routes. It can be mounted straight onto the ceiling or suspended using the appropriate accessories.

The cube shape means that this plastic luminaire is easily recognisable from four sides. Ideal for use where routes intersect, e.g. in large stores with aisles.

Wireless central control and monitoring for large installations of up to 50,000 luminaires with Wireless Professional. Planning certainty is provided by printed pictograms, determined on the basis of logic. The pictograms used correspond to DIN ISO 7010 (arrow to the right, left and down).

CE

5 JAHRE 5 YEARS GARANTIE WARRANTY

More information
www.rp-group.com/en/item/WKD418WL


TECHNICAL DATA


Luminaire type	Exit sign
Mounting	Surface mounting
Recognition distance	36 m
Pictograph	Set
Illuminant	LED
Housing material	Metal
Housing color	White
Protection type (IP)	IP20
Impact resistance (IK)	≥ 3
Certification	Waste disposal, CE, 5 Years waranty
Insulation class	1
Supply	Self-contained
Monitoring	Wireless Professional (WL)
Bridging time	8 h
Battery	LiFePO4 3,2 V/3,3 Ah
Operating mode	Non-maintained / maintained
Input voltage AC	230 V

Input frequency	50 Hz
Power max.	4,8 W
Power maintained	2,8 W
Power non-maintained	0,8 W
Ambient temperature maintained mode	-5 °C to 40 °C
Ambient temperature non-maintained mode	-5 °C to 40 °C
Depth	195 mm
Width	195 mm
Height	195 mm
Weight	0.87
Weight incl. packaging	1.01
Connection cross-section	2.5 mm²
Switching input	Yes
Emergency light blocking	Yes
Battery connection	Connector
Dimming function	Yes
Luminous flux mains	220 lm
Luminous flux emergency	470 lm
Customs tariff number	94056120
GTIN	4260766558603


RP GROUP
SOLUTIONS IN SAFETY + LIGHTING

TECHNICAL DRAWING







WK




WG



WX


25
138
25
25
70
ø 5
ø 20
ø 10
24
24
70
25
188
138
69
24
24
69
186
WK
25
180
25
25
90
ø 5
ø 20
ø 10
25
25
90
25
230
180
90
25
25
90
230
WG
45
402
45
45
220
ø 5
ø 20
ø 10
26
26
220
45
492
402
220
26
26
220
492
WX


195
195

ACCESSORY LIST

WKO - Set of chain eyelets for cube mounting (4 pieces)

1PV-EB - Pendulum

DSA-Y4M - Wire suspension

DSA-Y4M-APA - Wire suspension