




Art.-Nr: YMOCA-RELAIS8
CASA RELAIS8
CASA RELAIS8 has eight potential-free switch contacts

The CASA RELAIS8 is fitted with eight potential-free switch contacts. The maximum switching power stated can be realised independently for each of these contacts. Moreover, individual control of the eight contacts enables flexible applications. The extended "long-range" feature ensures reliable control over long distances too.



More information

www.rp-group.com/en/item/YMOCA-RELAIS8



TECHNICAL DATA

Dimensions	
Product dimensions Length	107 mm
Product dimensions Width	87,5 mm
Product dimensions Height	58,7 mm
Product weight	300 g
Color	
Color	White
Housing material	
Housing material	PCABS
Storage temperature range	
Storage temperature range (Min)	-25 °C
Storage temperature range (Max)	+75 °C
Housing temperature tc (Max)	
Housing temperature tc (Max)	+60 °C
Temperatures	
Ambient temperature (Min)	-20 °C
Ambient temperature (Max)	+50 °C
CASAMBI Products	
Input voltage AC	230 V



Input frequency	50 / 60 Hz
Power (Max)	2,5 W
External power supply unit	NO
Consumption in standby mode	0,8 W
Starting current	165 A
Load types	Capacitive load
Switching output	1380 W
Switching cycles	50000 pcs.
Communication type	CASAMBI
Frequency band	2,403 - 2,479 GHz
Max. transmission power	+8 dBm
CASAMBI Repeater	Yes
Protection type (IP)	IP20
Product.Casambi-Products.InsulationClass	2
Certifications	CE, RoHS

As of: 09.05.2026 - Subject to technical changes and errors.