RP GROUP
SOLUTIONS IN SAFETY + LIGHTING

Art.-Nr: KMB411WB-3P
Emergency light Self-contained Track system, Wireless Basic (WB), 1 h, IP54, Polycarbonate, White, 3-Phase railadapter



Compact safety luminaire for universal mounting. The narrow rectangular plastic housing is discreetly reduced to the essentials. Illumination of the escape and emergency routes is assisted by the optics integrated in the surround.

Wireless control and monitoring for small installations of up to 50 luminaires with Wireless Basic. The pre-mounted 3-phase adapter allows for tool-free installation in popular 3-phase tracks, such as Nordic Aluminium GLOBAL pro (previously NOKIA) XTS, XTTS and XTSC.

CE

5 JAHRE 5 YEARS GARANTIE WARRANTY


More information
www.rp-group.com/en/item/KMB411WB-3P

TECHNICAL DATA

Luminaire type	Emergency light
Mounting	Track system
Pictograph	No
Illuminant	LED
Housing material	Polycarbonate
Housing color	White
Protection type (IP)	IP54
Impact resistance (IK)	≥ 3
Certification	Waste disposal, CE, 5 Years waranty
Insulation class	2
Supply	Self-contained
Monitoring	Wireless Basic (WB)
Bridging time	1 h
Battery	LiFePO4 3,2 V/1,6 Ah
Operating mode	Non-maintained / maintained
Input voltage AC	230 V
Input frequency	50 / 60 Hz
Input voltage DC	- V
Power max.	5,3 W

Power maintained	3,9 W
Power non-maintained	1,5 W
Ambient temperature maintained mode	-10 °C to 40 °C
Ambient temperature non-maintained mode	-5 °C to 40 °C
Depth	250 mm
Width	34 mm
Height	50 mm
Weight	0.55
Weight incl. packaging	0.62
Connection cross-section	2.5 mm²
Switching input	Yes
Emergency light blocking	No
Battery connection	Connector
Dimming function	No
Luminous flux mains	190 lm
Luminous flux emergency	190 lm
Customs tariff number	94056180
GTIN	4262483020371

TECHNICAL DRAWING



ACCESSORY LIST

KME-EB - Mounting frame

BALL1 - Wire mesh guard

KMBE - Concrete-mounted box

BALLPLX-KMB - Ball impact-resistant protective cover (PMMA) transparent for lights - KMB

KMBFH - Customisable positioning for optimal emergency exit lighting – 249 x 40 mm

LFPN3216.01 - Battery

As of: 13.11.2026 - Subject to technical changes and errors.