RP GROUP
SOLUTIONS IN SAFETY + LIGHTING

Art.-Nr: KMU413WL-3P
Exit sign Self-contained
Track system, Wireless Professional (WL), 3 h, 24 m, IP43, Polycarbonate, White, Set of pictograms, Universal mounting



Slim convex emergency exit sign luminaire with 3-phase adapter. Planning certainty for identifying escape and emergency routes for inscription on one or two sides is provided by tool-free variable use of the pictograms on site. The pictograms are inserted without the use of solvents. The set of pictograms (arrow to the right, left, up or down) is supplied as standard.

The pre-mounted 3-phase adapter allows for tool-free installation in popular 3-phase tracks, such as Nordic Aluminium GLOBAL pro (previously NOKIA) XTS, XTTS and XTSC.

Emergency exit sign luminaire in accordance with DIN EN 60598-1, DIN EN 60598-2-22 and DIN EN 1838.

Wireless central control and monitoring for large installations of up to 50,000 luminaires with Wireless Professional. Planning certainty is provided by tool-free, variable use of the pictograms on site. A set of pictograms corresponding to DIN ISO 7010 (arrow to the right, left, up and down) is supplied as standard. Universal mounting includes fitting on the wall and ceiling as well as the option of fitting in the ceiling in conjunction with the mounting frame available.

CE

5 JAHRE 5 YEARS GARANTIE WARRANTY


More information
www.rp-group.com/en/item/KMU413WL-3P

TECHNICAL DATA

Luminaire type	Exit sign
Mounting	Track system
Recognition distance	24 m
Pictograph	Set
Illuminant	LED
Housing material	Polycarbonate
Housing color	White
Protection type (IP)	IP43
Impact resistance (IK)	3
Certification	Waste disposal, CE, 5 Years waranty
Insulation class	2
Supply	Self-contained

Monitoring	Wireless Professional (WL)
Bridging time	3 h
Battery	LiFePO4 3,2 V/1,6 Ah
Operating mode	Non-maintained / maintained
Input voltage AC	230 V
Input frequency	50 / 60 Hz
Input voltage DC	- V
Power max.	5,3 W
Power maintained	3,9 W
Power non-maintained	1,5 W
Ambient temperature maintained mode	-5 °C to 35 °C
Ambient temperature non-maintained mode	-5 °C to 35 °C
Depth	34 mm
Width	250 mm
Height	174 mm
Weight	0.42
Weight incl. packaging	0.59
Connection cross-section	2.5 mm²
Switching input	Yes
Emergency light blocking	No
Battery connection	Connector
Dimming function	No
Luminous flux mains	190 lm
Luminous flux emergency	190 lm
Customs tariff number	94056120
GTIN	4262483020227

TECHNICAL DRAWING



ACCESSORY LIST

LFP3233.01 - Battery

As of: 11.11.2026 - Subject to technical changes and errors.