RP GROUP
SOLUTIONS IN SAFETY + LIGHTING

Art.-Nr: QAW423WB-BM
General light, Emergency light Self-contained Universal, Wireless Basic (WB), 3 h, IP20, Aluminum, White, HF motion detector



Round aluminium LED luminaire, general-purpose luminaire with integrated safety light function for illuminating escape and emergency routes.

Wireless control and monitoring for small installations of up to 50 luminaires with Wireless Basic. The integrated motion detector **(BM)** reliably detects movements and automatically turns on the light in mains operation.

CE

5 JAHRE 5 YEARS GARANTIE WARRANTY

More information
www.rp-group.com/en/item/QAW423WB-BM

TECHNICAL DATA


Luminaire type	General light, Emergency light
Mounting	Universal
Pictograph	No
Illuminant	LED
Housing material	Aluminum
Housing color	White
Protection type (IP)	IP20
Impact resistance (IK)	≥ 3
Certification	Waste disposal, CE, 5 Years waranty
Insulation class	1
Supply	Self-contained
Monitoring	Wireless Basic (WB)
Bridging time	3 h
Battery	LiFePO4 3,2 V/3,3 Ah
Operating mode	Non-maintained / maintained
Input voltage AC	230 V
Input frequency	50 / 60 Hz
Power max.	30 W
Power maintained	26,4 W
Power non-maintained	0,4 W



RP GROUP
SOLUTIONS IN SAFETY + LIGHTING

Ambient temperature maintained mode	-5 °C to 30 °C
Ambient temperature non-maintained mode	-5 °C to 35 °C
Height	113 mm
Diameter	395 mm
Weight	2.18
Weight incl. packaging	2.5
Connection cross-section	2.5 mm²
Switching input	Yes
Emergency light blocking	No
Battery connection	Connector
Dimming function	Yes
Luminous flux mains	2300 lm
Luminous flux emergency	250 lm
EOF	0.11
Customs tariff number	94056180
GTIN	4262483024201

TECHNICAL DRAWING



As of: 15.11.2026 - Subject to technical changes and errors.