RP GROUP
SOLUTIONS IN SAFETY + LIGHTING

Art.-Nr: QAW428WB
General light, Emergency light Self-contained Universal, Wireless Basic (WB), 8 h, IP20, Aluminum, White



Round aluminium LED luminaire, general-purpose luminaire with integrated safety light function for illuminating escape and emergency routes.

Wireless control and monitoring for small installations of up to 50 luminaires with Wireless Basic.

CE 5 JAHRE 5 YEARS GARANTIE WARRANTY


More information
www.rp-group.com/en/item/QAW428WB

TECHNICAL DATA

Luminaire type	General light, Emergency light
Mounting	Universal
Pictograph	No
Illuminant	LED
Housing material	Aluminum
Housing color	White
Protection type (IP)	IP20
Impact resistance (IK)	≥ 3
Certification	Waste disposal, CE, 5 Years waranty
Insulation class	1
Supply	Self-contained
Monitoring	Wireless Basic (WB)
Bridging time	8 h
Battery	LiFePO4 3,2 V/3,3 Ah
Operating mode	Non-maintained / maintained
Input voltage AC	230 V
Input frequency	50 / 60 Hz
Power max.	30 W
Power maintained	26,4 W
Power non-maintained	0,4 W
Ambient temperature maintained mode	-5 °C to 30 °C
Ambient temperature non-maintained mode	-5 °C to 35 °C

Height	113 mm
Diameter	395 mm
Weight	2.18
Weight incl. packaging	2.5
Connection cross-section	2.5 mm²
Switching input	Yes
Emergency light blocking	No
Battery connection	Connector
Dimming function	Yes
Luminous flux mains	2300 lm
Luminous flux emergency	125 lm
EOF	0.05
Customs tariff number	94056180
GTIN	4262483024232

TECHNICAL DRAWING



As of: 15.11.2026 - Subject to technical changes and errors.