Art.-Nr: QAW029ML-WW
General light, Emergency light Centralised power supply systems
Universal, Central power supply (ML), CPS, IP20, Aluminum, White



Round metal luminaire for general-purpose lighting and illuminating escape and emergency routes in accordance with DIN EN 60598-1, DIN EN 60598-2-22 and DIN EN 1838.

This luminaire is designed for central battery operation. In mains operation, the LED luminaire is run at 26W, 2300lm, 4000 K.

The performance data stated relates to the in-built emergency luminaire.

Control and monitoring via central power supply system.


More information
www.rp-group.com/en/item/QAW029ML-WW

TECHNICAL DATA

Luminaire type	General light, Emergency light
Mounting	Universal
Pictograph	No
Illuminant	LED
Housing material	Aluminum
Housing color	White
Protection type (IP)	IP20
Impact resistance (IK)	≥ 3
Certification	Waste disposal, CE
Insulation class	1
Supply	Centralised power supply systems
Monitoring	Central power supply (ML)
Bridging time	CPS
Battery	/
Operating mode	single luminaire switching
Input voltage AC	230 V
Input frequency	50 / 60 Hz
Input voltage DC	216 V
Power max.	30,6 W

Power maintained	27,2 W
Power non-maintained	1,2 W
Ambient temperature maintained mode	-20 °C to 30 °C
Ambient temperature non-maintained mode	-20 °C to 40 °C
Height	113 mm
Diameter	395 mm
Weight	2.1
Weight incl. packaging	2.42
Connection cross-section	2.5 mm²
Switching input	No
Emergency light blocking	No
Battery connection	No
Dimming function	Yes
Luminous flux mains	2300 lm
Luminous flux emergency	360 lm
EOF	0.16
Customs tariff number	94056180
GTIN	4262483024645

TECHNICAL DRAWING



As of: 15.11.2026 - Subject to technical changes and errors.