
Art.-Nr: YMOCA-SAL-2032
Salvador 2032
Capable of managing up to 32 DALI driver addresses with integrated DALI bus power supply



The Salvador Series 2000 seamlessly integrates wired DALI drivers into the Casambi system. When integrated, DALI luminaires appear as luminaires in the Casambi network. Notably, this product supports industry standards such as DALI D4i, DALI DT6, and DALI DT8.

The Salvador Series 2000 is only for connecting to DALI drivers. No DALI controls must be connected to Salvador Series 2000 products.

The Salvador Series 2000 has integrated 130 mA bus power supply for the DALI operation.

More information
www.rp-group.com/en/item/YMOCA-SAL-2032

TECHNICAL DATA

Dimensions	
Product dimensions Length	127 mm
Product dimensions Width	67 mm
Product dimensions Height	28 mm
Product weight	120 g
Color	
Color	White
Housing material	
Housing material	Polycarbonate
Storage temperature range	
Storage temperature range (Min)	-25 °C
Storage temperature range (Max)	+75 °C
Housing temperature tc (Max)	
Housing temperature tc (Max)	+55 °C
Temperatures	
Ambient temperature (Min)	-20 °C
Ambient temperature (Max)	+50 °C
CASAMBI Products	

Input vokltage AC	230 V
Input frequency	50 / 60 Hz
External power supply unit	No
Communication type	Bluetooth, CASAMBI, DALI 1, DALI 2
Frequency band	2,403 - 2,479 GHz
Max. transmission power	+8 dBm
BMS	DALI
DALI bus supply	Yes
DALI bus voltage	12 - 15 VDC
DALI output current	130
Number of DALI addresses	32 pcs.
CASAMBI Repeater	Yes
Certifications	CE
CASAMBI Connection	
Connection cross-section	1,5 mm²