



Art.-Nr: ERZL-WSC13

Exit sign, Emergency light Self-contained

Wall mounting, 3 h, 16 m, IP65, Polycarbonate, White, Set of pictograms

Classic, robust, plastic, beam-like emergency exit sign luminaire with a high level of protection and self-adhesive pictogram for versatile use.

Intended for wall mounting when used as an emergency exit sign luminaire.

Without the use of pictograms, it can be used as a safety luminaire, preferably for ceiling mounting.

Automatic monitoring of safety luminaire with SelfControl. Planning certainty is provided by tool-free, variable use of the pictograms on site. A set of pictograms corresponding to DIN ISO 7010 (arrow to the right, left, up and down) is supplied as standard.



More information

www.rp-group.com/en/item/ERZL-WSC13



TECHNICAL DATA


Luminaire type	Exit sign, Emergency light
Mounting	Wall mounting
Recognition distance	16 m
Pictograph	Set
Illuminant	LED
Housing material	Polycarbonate
Housing color	White
Protection type (IP)	IP65
Impact resistance (IK)	6
Certification	CE, WEEE, D-Sign
Insulation class	2
Supply	Self-contained
Monitoring	SelfControl (SC)
Bridging time	3 h
Battery	NIMH 4,8 V/2,0 Ah
Operating mode	Non-maintained / maintained
Input voltage AC	230 V



Input frequency	50 / 60 Hz
Power max.	6,17 W
Power maintained	4,6 W
Power non-maintained	0,35 W
Ambient temperature maintained mode	-5 °C to 35 °C
Ambient temperature non-maintained mode	-5 °C to 35 °C
Depth	86 mm
Width	390 mm
Height	99 mm
Weight	0.79
Weight incl. packaging	0.89
Connection cross-section	2.5 mm ²
Switching input	Yes
Emergency light blocking	Yes
Battery connection	Connector
Dimming function	Yes
Luminous flux mains	300 lm
Luminous flux emergency	230 lm
EOF	0.77
Customs tariff number	94056120
GTIN	4003899943508



TECHNICAL DRAWING



ACCESSORY LIST

- BKW - Robust steel protective grille for emergency lighting
- KWIE - Installation frame
- NIMHHT4820Q - Battery

As of: 24.07.2026 - Subject to technical changes and errors.