



Art.-Nr: KAMK403SC
Exit sign Self-contained
Universal, 22 m, IP65, Polycarbonate, White, Set of
pictograms, Universal mounting

Plastic emergency exit sign luminaire for universal mounting. The cuboid plastic housing is discreetly reduced to the essentials. The high level of protection permits use in damp rooms or highly contaminated environments.

Automatic monitoring of safety luminaire with SelfControl. Display edge luminaire with integrated light distribution for even pictogram illumination. Suited to inscription on one or two sides. Planning certainty is provided by tool-free, variable use of the pictograms on site. A set of pictograms corresponding to DIN ISO 7010 (arrow to the right, left, up and down) is supplied as standard. Universal mounting includes the option of mounting the luminaire either on the wall or ceiling.



More information
www.rp-group.com/en/item/KAMK403SC



TECHNICAL DATA


Luminaire type	Exit sign
Mounting	Universal
Recognition distance	22 m
Pictograph	Set
Illuminant	LED
Housing material	Polycarbonate
Housing color	White
Protection type (IP)	IP65
Impact resistance (IK)	7
Certification	WEEE, CE
Insulation class	2
Supply	Self-contained
Monitoring	SelfControl (SC)
Battery	LiFePO4 3,2 V/1,6 Ah
Operating mode	Non-maintained / maintained
Power max.	3,7 W
Power maintained	2,4 W



Power non-maintained	0,3 W
Ambient temperature maintained mode	0 °C to 35 °C
Ambient temperature non-maintained mode	0 °C to 35 °C
Depth	326 mm
Width	50 mm
Height	204 mm
Weight	0.1
Weight incl. packaging	0.3
Connection cross-section	1,5 mm ²
Switching input	Yes
Emergency light blocking	No
Battery connection	Connector
Dimming function	No
Customs tariff number	94056180
GTIN	4260682157638



TECHNICAL DRAWING



ACCESSORY LIST

AWX001 - AWX wall bracket for emergency lights - 90° flag mounting

2PW-EB - Pendant

2DW-EB - Pre-assembled designer pendant pair with fixed canopy, 4-core, white

As of: 21.07.2026 - Subject to technical changes and errors.