



Art.-Nr: PXDL529CC

**Emergency light Centralised power supply systems
Surface mounting, CPS, IP65, PCABS, Polycarbonate, White,
Flexiklick**

Robust plastic emergency light with a high protection rating in a linear design for versatile use.

Suitable for maintained or non maintained mode.

Control and monitoring via central 24 V low-power system. The luminaire is fitted with the innovative flexible plug-in system for rapid use of the right lens. The corridor lens is supplied with every luminaire. A round lens, spotlight lens and beam lens are available as options.



More information
www.rp-group.com/en/item/PXDL529CC




TECHNICAL DATA

Luminaire type	Emergency light
Mounting	Surface mounting
Pictograph	No
Illuminant	LED
Housing material	PCABS, Polycarbonate
Housing color	White
Protection type (IP)	IP65
Impact resistance (IK)	8
Certification	WEEE, CE, D-Sign
Insulation class	2
Supply	Centralised power supply systems
Monitoring	CoreCompact 24 (CC)
Bridging time	CPS
Battery	/
Operating mode	Non-maintained / maintained
Input voltage AC	24 V
Power max.	5,1 W
Power maintained	5,1 W
Power non-maintained	0,4 W



Ambient temperature maintained mode	-20 °C to 50 °C
Ambient temperature non-maintained mode	-20 °C to 50 °C
Depth	73 mm
Width	339 mm
Height	71 mm
Weight	0.63
Weight incl. packaging	0.73
Connection cross-section	2.5 mm ²
Switching input	No
Emergency light blocking	No
Battery connection	No
Luminous flux mains	520 lm
Luminous flux emergency	520 lm
Customs tariff number	94056120
GTIN	4262483026649

TECHNICAL DRAWING





ACCESSORY LIST

PXD-AW - Parallel wall bracket for the PXD emergency and safety light

As of: 24.08.2026 - Subject to technical changes and errors.