



Art.-Nr: WLREP3 Wireless Professional Repeater Greater range

Wireless Professional Repeater

Optimizes connections indoors or outdoors. It is used in areas with poor reception or in large installations. The range to the nearest Wireless Professional device, like the range of the lights, is at least 30 meters indoors. The Wireless Professional repeater is supplied in an IP65 housing.

Repeater for the Wireless Professional automatic test system in the 868 MHz band according to ETSI EN 300 220



More information
www.rp-group.com/en/item/WLREP3



TECHNICAL DATA

Material	Polycarbonate
Housing color	Light grey
Depth	76 mm
Width	116 mm
Height	162 mm
Weight	0.42 kg
Customs tariff number	85176200
GTIN	4262483026717



Technical drawing of the ESD-1000 enclosure, showing multiple views with dimensions in mm:

- Top View:** Overall dimensions 179.9 mm (width) x 133.1 mm (depth). Internal width is 166.5 mm. Mounting hole spacing is 43.5 mm. Mounting holes are Ø25. A central circular feature has a diameter of Ø40.
- Front View:** Overall height is 96.3 mm. Internal height is 108 mm. Mounting hole spacing is 77.7 mm. Mounting holes are Ø25. A central circular feature has a diameter of Ø40.
- Side View:** Overall width is 153.4 mm. Internal width is 128.2 mm. Mounting hole spacing is 147.7 mm. Mounting holes are Ø25. A central circular feature has a diameter of Ø40.
- Bottom View:** Overall dimensions 179.9 mm (width) x 133.1 mm (depth). Internal width is 166.5 mm. Mounting hole spacing is 43.5 mm. Mounting holes are Ø25. A central circular feature has a diameter of Ø40.
- Isometric View:** Shows the enclosure from an isometric perspective, highlighting its compact design and mounting features.
- Detail View:** Shows a close-up of the mounting holes, with dimensions 25.5 mm (hole diameter), 15.8 mm (hole spacing), and 38.5 mm (hole diameter).
- Mounting Hole Detail:** Shows a close-up of the mounting holes, with dimensions 25.5 mm (hole diameter), 15.8 mm (hole spacing), and 38.5 mm (hole diameter).
- Mounting Hole Detail (4x):** Shows a close-up of the mounting holes, with dimensions 25.5 mm (hole diameter), 15.8 mm (hole spacing), and 38.5 mm (hole diameter).

www.rp-group.com