RP GROUP
SOLUTIONS IN SAFETY + LIGHTING

Art.-Nr: MIUS02
microControl plus Substation Wall housing
Substation, Wall housing, 2 circuits, 1h/1300 W - 3h/1300 W - 8h/1300 W



The microControl plus Substation MIUS is a versatile power supply system compliant with DIN EN 50171, designed to supply safety and emergency exit luminaires with 230 V / 216 V AC/DC. It is suitable for emergency lighting systems in accordance with DIN VDE 0100-560, DIN EN 50172, and DIN VDE V 0108-100, and can be equipped with up to 6 freely programmable circuits in a service-friendly 19" modular rack system.

With its integrated automatic test device, the system can reliably supply, monitor, and manage up to 120 luminaires. Furthermore, up to 32 systems can be networked via TCP/IP.

More information
www.rp-group.com/en/item/MIUS02

TECHNICAL DATA

Inserts	3 pcs.
Number of DCM modules	1 pcs.
Number of circuits	2
Charger	No
Modules SAM	Yes
IO modules	Yes
CCIF	Yes
Networkable	Yes
Outgoing SS/SD	No
Battery compartment	No
Supply power 1 h	1300 W
Supply power 3 h	1300 W
Supply power 8 h	1300 W
Input voltage AC	230 V
Input frequency	50 / 60 Hz
Output voltage AC	230 V
Material	Steel sheet



Housing color	Light grey
Insulation class	IP20
Depth	230 mm
Width	350 mm
Height	430 mm
Weight	9 kg
Weight incl. packaging	9 kg
Customs tariff number	85371098
Max. Output voltage DC	216 V