Art.-Nr: LFU12403SC-CCT-D
Emergency light, General light Self-contained Wall mounting, Surface mounting, SelfControl (SC), 3 h, IP66, Polycarbonate, Light grey



LED diffuser, VASCA series. Polycarbonate housing. Prismatic diffuser made of UV-resistant PC. The diffuser is attached with stainless steel clips. The LED circuit board is individually replaceable. The luminaire also features through-wiring.

The wattage (18-36W) and color temperature (3000 - 4000 - 5000K) are individually adjustable via DIP switches.

Automatic monitoring of safety luminaire with SelfControl. The luminaire is equipped with a DALi driver (D), which allows it to be integrated into the Dali lighting control system.

CE


More information
www.rp-group.com/en/item/LFU12403SC-CCT-D

TECHNICAL DATA

Luminaire type	Emergency light, General light
Mounting	Wall mounting, Surface mounting
Pictograph	No
Housing material	Polycarbonate
Housing color	Light grey
Protection type (IP)	IP66
Impact resistance (IK)	8
Certification	CE, Waste disposal
Insulation class	1
Supply	Self-contained
Monitoring	SelfControl (SC)
Bridging time	3 h
Battery	LiFePO4 3,2 V/
Operating mode	Non-maintained / maintained
Input voltage AC	220 V - 240 V
Input frequency	50 / 60 Hz

Power max.	39 W
Power maintained	36 W
Power non-maintained	0,7 W
Ambient temperature maintained mode	-5 °C to 40 °C
Ambient temperature non-maintained mode	-5 °C to 40 °C
Depth	1220 mm
Width	82 mm
Height	97 mm
Weight	2.08
Weight incl. packaging	2.33
Connection cross-section	1,5 mm²
Switching input	Yes
Emergency light blocking	No
Battery connection	Connector
Dimming function	Yes
Luminous flux mains	5040 lm
Luminous flux emergency	530 lm
EOF	0.11
Customs tariff number	94051140
GTIN	4262483029824

TECHNICAL DRAWING



As of: 08.11.2026 - Subject to technical changes and errors.